

Smart Industrial Connectivity

Core Portfolio - New Zealand

Issue #1



**Your Partner in
Smart Industrial Connectivity**

Weidmüller 

Portfolio overview

Power supplies

Industrial Ethernet

Access Port / FrontCom


Remote Access:
Maintenance & Cloud Serv

Remote I/O

Transformer terminal block

Relay modules
& solid-state relays

Power distribution



DC Power distribution

maxGUARD

Energy monitoring

Terminal blocks

RJ45 Patch Cords

analogue signal conditioning

Surge protection

Heavy duty connectors


Markers

Configuration Software



Weidmüller Configurator

- Simplifies configuration and ordering for extra efficiency in panel planning, installation and operation
- Minimization of failures
- User-friendly
- Easy documentation



Product Configuration / Selection Software

- Competitive cross-reference database
- Configure custom PCBs, rectangular connectors, Ethernet cabling and connectors, SAI cordsets and connectors

Weidmüller Configurator

Simple and seamless planning tool



Digital engineering can be as simple as that! Create your configuration from over 12,000 digital Weidmüller products.

The Weidmüller Configurator (WMC) is a configuration tool for seamless and secure planning of electrical systems as well as simple procurement and assembly of complete solutions.

Unlock your potential of automated production from paperless production all the way up to automatic manufacturing - in just one tool.

Find more information about the Weidmüller Configurator here:











Table of contents


4	PUSH IN technology (A-Series)
7	Screw technology (W-Series)
8	Tension clamp technology (Z-Series)
9	Terminal Accessories
10	Power Supplies
11	DC UPS & DC/DC Converter
12	Electronic Fuse
13	Industrial Ethernet Switches
14	Rackmount switches, routers and IOT
15	Industrial Ethernet Connectivity
17	Remote IO & Controllers
18	Energy Metering
19	Termseries PLC Relays
20	General Relays
21	Signal Conditioning
22	Process Displays
23	Surge Protection
24	Heavy Duty Connectors
25	Circular Cordsets
26	Tools
28	Ferrules
29	Markers and printers
31	Cable Entry Systems

PUSH IN technology (A-Series)

Build with the best with Weidmüller's Klippon Connect range. It's our unwavering commitment to quality that has made Weidmüller the name synonymous with terminals in Australia & New Zealand for over 50 years.




Series / family	mm ²	Connections per level	Levels	Application	Description	Standard	Blue	Earth	End Plate
A-series PUSH IN          	1.5	2	1	Feed Through	A2C 1.5	1552790000	1552820000	1552680000	1552600000
			2		A2T 1.5	2469370000	2471430000	2469410000	2469420000
			3		A3T 1.5	2816930000	2816940000	2818000000	2816950000
			1		A2C 2.5	1521850000	1521880000	1521680000	1514400000
			2	Disconnect	A2T 2.5	1547610000	1547620000	1547680000	1547690000
			1		ADT 2.5 2C	1989800000	1989810000	-	1521530000
	2.5	3	2		A2T 2.5 DT/DT	2744110000	2744120000	-	2744150000
			3	Feed Through	A3T 2.5	2428510000	2428520000	2428550000	2428560000
			1		A3C 2.5	1521740000	1521780000	1521670000	1521510000
			4		A4C 2.5	1521690000	1521700000	1521540000	1521530000
			1	Disconnect	A2C 4	2051180000	2051210000	2051360000	2051680000
			2		ADT 4 2C	2429850000	2429880000	-	2051720000
	4	2	2		A2T 4 DT-FT	2831520000	-	-	2817060000
			1	Sensors & Actuator	A2T 4 DT-FT-PE	2831530000	-	-	
			2		AFS 4 2C BK	2429860000	-	-	
			1		AFS 4 2C 10-36V BK	2429870000	-	-	2486640000
			2	Fuse (5x20)	AFS 4 2C 100-250V BK	2434390000	-	-	
			1		A2T 4 FS-FT BK	2816960000	-	-	
			2		A2T 4 FS-FT-PE BK	2817010000	-	-	2817060000
			1		A2T 4 FS-FT 10-36V BK	2816970000	-	-	
			2	Sensors & Actuator	A2T 4 FS-FT-PE 10-36V BK	2817020000	-	-	
			3		A3C 4	2051240000	2051280000	2051410000	2051720000
			4		A4C 4	2051500000	2051520000	2051560000	2051900000
			2	Feed Through	A2T 4	2539970000	2540040000	2539990000	2540000000
			1		A2C 6	1992110000	1991790000	1991810000	1991970000
			2		A3C 6	1991820000	1991830000	1991850000	1991940000
			1		A2C 10	2490360000	2490370000	2490440000	2490380000
			2		A3C 10	2490520000	2490510000	2490590000	2490530000
			1		A2C 16	2494000000	2494100000	2494010000	2490380000
			2		A3C 16	2494090000	2494080000	2494020000	2490530000
			1		A2C 35	2551510000	2552090000	2551520000	
			2		3-phase + N	2552130000	-	-	
			1		3-phase + N + PE	2551540000	-	-	
A-Series High Current 	35	2	1	Feed Through	A2C 35	2551510000	2552090000	2551520000	Not Required
		8		3-phase + N	A2C 35 3FT-N	2552130000	-	-	
		10		3-phase + N + PE	A2C 35 3FT-N-PE	2551540000	-	-	
	50/70	2		Feed Through	A2C 50/70	2663250000	2663260000	2663280000	
		8		3-phase + N	A2C 50/70 3FT-N	2663300000	-	-	
		2		Feed Through	A2C 95/120	2694060000	2694070000	2694090000	
	95/120	8		3-phase + N	A2C 95/120 3FT-N	2694120000	-	-	
		8							

Series / family	mm ²	Colour	2-pole	3-pole	4-pole	5-pole	10-pole	20-pole	50-pole
ZQV Cross- connectors   	1.5	Orange	1985410000	1985480000	1985490000	1985500000	1985580000	1985600000	1985620000
		Red	1985650000	1985670000	1985690000	1985710000	1985800000	1985810000	1985590000
		Blue	1985530000	1985550000	1985570000	1985590000	1985680000	1985700000	1985720000
	2.5	Orange	1527540000	1527570000	1527590000	1527620000	1527690000	1527720000	1527730000
		Red	2108470000	2108690000	2108700000	2108710000	2108910000	2108920000	2109000000
		Blue	1527740000	1527770000	1527780000	1527790000	1527880000	1527890000	1527920000
	4	Orange	1527930000	1527940000	1527970000	1527980000	1528090000	2883800000	1528130000
		Red	2460450000	2460810000	2460800000	2460790000	2460740000	2810860000	2460730000
		Blue	1528040000	1528080000	1528120000	1528140000	1528230000	2810850000	1528240000
	6	Orange	1985740000	1985760000	1985780000		2733970000		
	10		2497250000						
	16		2497290000						
	35		2634950000						
	50/90		2663400000						
	95/120		2694250000						

PUSH IN technology (A-Series)

Klippon A-Series with side PUSH IN connection. Enjoy the advantages of PUSH IN technology with the increased wiring visibility and decreased installation height with side-entry wiring.



Series / family	mm ²	Connections per level	Levels	Application	Description	Standard	Blue	Earth	End Plate
AL-Series PUSH IN Side Entry		2	1	Feed Through	AL2C 2.5	2847200000	2847210000	2847590000	2871750000
		3			AL3C 2.5	2847330000	2847340000	2847600000	2871770000
		4			AL4C 2.5	2847460000	2847470000	2847610000	2871790000
		2		Disconnect	ALDT 2.5 2C	2898660000	2898670000	-	2898830000
		3			ALDT 2.5 3C	2898700000	2898710000	-	2898850000
		2		Feed Through	AL2C 4	2847710000	2871870000	2847740000	2871810000
		3			AL3C 4	2847720000	2871990000	2847750000	2871830000
		4			AL4C 4	2847730000	2872110000	2847770000	2871850000
		2			ALDT 4 2C	2898740000	2898750000	-	2898890000
		2		Fuse (5x20)	ALFS 4 2C BK	2898780000	-	-	2898890000

● Available Q4 2023

Series / family	mm ²	Connections	Application	Description	Standard	End Plate
Control Voltage Distribution PUSH IN A-Series		1 x 6mm ² 6 x 1.5mm ²	Feed in + Distribution	AAP11 6/6X1.5 LO-LI RED	2464690000	1988320000
			Earth Terminal	AAP11 6/6X1.5 PE-LI	2464750000	
		6 x 1.5mm ²	Extension Terminals	AAP11 1.5 LI RED	2464740000	
			Extension Terminals	AAP11 1.5 LI BLUE	1988160000	
		1 x 10mm ² 4 x 2.5mm ²	Feed in + Distribution	AAP11 1.5 LI GN/OR	1988170000	1988300000
			Feed in + Distribution	AAP12 10/4X2.5 LO-LI RED	2614100000	
			Earth Terminal	AAP12 10/4X2.5 LO-LI BLUE	2464730000	
		5 x 2.5mm ²	Extension Terminals	AAP12 10/4X2.5 PE-LI	2464720000	
			Extension Terminals	AAP12 2.5 LI BLUE	2464710000	
			Extension Terminals	AAP12 2.5 LI RED	1988100000	
			Extension Terminals	AAP12 2.5 LI GN/OR	1988290000	
			Extension Terminals	AAP12 2.5 LI GN/OR	2614110000	

Series / family		mm²	Connections	Levels	Application	Description	Standard	End Plate
Signal Wiring PUSH IN A-Series		1.5	2	2	Instrumentation Wiring	AIQ21 1.5 SO	1992240000	1993580000
			3	AIQ21 1.5 SI		1992260000		
			6	3		AIQ23 1.5 2SI	1992220000	1993600000


Weidmüller's revolutionary SNAP IN technology is extremely easy to use. Stranded cables with no ferrules can be directly inserted without tools. The connection snaps shut with a click - just like a mouse trap.

Series / family		mm²	Connections per level	Levels	Application	Description	Standard	Blue	Earth	End Plate
S-Series SNAP IN	 S2C S2T	2.5	2	1	Stranded cable without ferrule	S2C 2.5	2674530000	2753940000	2674560000	2751080000
			3			S3C 2.5	2674540000	2753950000	2674570000	2751090000
			4			S4C 2.5	2674550000	2753960000	2674580000	2751100000
			2			S2T 2.5	2902380000	2902390000	2902460000	2902630000
		4	2	S2C 4		2874820000	2874830000	2874880000	2874790000	
			3	S3C 4		2874840000	2874850000	2874890000	2874800000	
			4	S4C 4		2874860000	2874870000	2874900000	2874810000	
			4	S4C 4		2874860000	2874870000	2874900000	2874810000	

● Available Q4 2023

Series / family	mm ²	Colour	2-pole	3-pole	4-pole	5-pole	10-pole	20-pole	50-pole
ZQV Cross- connectors		Orange	1985410000	1985480000	1985490000	1985500000	1985580000	1985600000	1985620000
		Red	1985650000	1985670000	1985690000	1985710000	1985800000	1985810000	1985820000
		Blue	1985530000	1985550000	1985570000	1985590000	1985680000	1985700000	1985720000
		Orange	1527540000	1527570000	1527590000	1527620000	1527690000	1527720000	1527730000
		Red	2108470000	2108690000	2108700000	2108710000	2108910000	2108920000	2109000000
		Blue	1527740000	1527770000	1527780000	1527790000	1527880000	1527890000	1527920000
		Orange	1527930000	1527940000	1527970000	1527980000	1528090000	2883800000	1528130000
		Red	2460450000	2460810000	2460800000	2460790000	2460740000	2810860000	2460730000
		Blue	1528040000	1528080000	1528120000	1528140000	1528230000	2810850000	1528240000

See page 29 for marking solutions







PUSH IN technology (A-Series)





TTB current transformer test/disconnect terminals. Isolate current transformers safely and easily with the Klippon TTB series. Featuring new make-before-break functionality, CT testing and maintenance can be performed as simple as turning a switch!

Series / family	mm²	Phases	Application	Screw Terminal	Part Number	PUSH-IN	Part Number
TTB Current transformer disconnect kits		1	Single phase CT metering	WTTB CT KIT 1PH	7940127529	ATTB CT KIT 1PH	7940127934
		3	3-phase CT metering with or without earth	WTTB CT KIT 3PH	7940127530	ATTB CT KIT 3PH	7940127935
		3+E		WTTB CT KIT 3PH+E	7940127531	ATTB CT KIT 3PH+E	7940127936
		3+N+E	3 Phase + Neutral CT metering with earth	WTTB CT KIT 3PH+N+E	7940127938	ATTB CT KIT 3PH+N+E	7940127937
		3+E+VT	3 Phase CT + voltage feedthrough metering with earth	WTTB CT KIT 3PH+E+VT	7940127532	ATTB CT KIT 3PH+E+VT	7940128855

Series / family	Matching Terminal	Description	Part Number
Accessories Partition Plates	A2C 1.5, A2C 2.5	APP 1	2488970000
	A3C 1.5, A4C 1.5, A3C 2.5, A4C 2.5, A2C 4, A3C 4, A2C 6, ADT 4	APP 2	2489090000
	A3C 6, AAP11, AAP13, AIO21	APP 3	2489100000
	A2T 1.5, A2T 2.5	APP 4	2489110000

Series / family	Matching Terminal	Description	Part Number
Accessories Warning Labels	1.5mm²	AAM 1.5 YELLOW FLASH	2635520000
	2.5mm²	AAM 2.5 YELLOW FLASH	2635550000
	4mm²	AAM 4 YELLOW FLASH	2635560000
	6mm²	AAM 6 YELLOW FLASH	2635570000
	10mm²	AAM 10 YELLOW FLASH	2635580000
	16mm²	AAM 16 YELLOW FLASH	2635590000
	35-185mm²	AAM 35-185 YELLOW FLASH	2635600000

Wiring of current transformer and ammeter


Switching the lever link

Replacing the ammeter

Restoring the lever link back into original position

Screw technology (W-Series)

We set the standard for screw clamp technology. Our W-Series range has been the most popular and reliable screw connection terminal favoured across Australia & New Zealand for more than 50 years.



Series / family	mm ²	Connections per level	Levels	Application	Description	Standard	Blue	Earth	End Plate
W-series Screw Terminal	2.5	2	1	Feed Through	WDU 2.5 ●●	1020000000	1020080000	1010000000	1050000000
			2		WDK 2.5 ●	1021500000	1021580000	1036300000	1059100000
			3		WDK 2.5 ZQV ●	1041100000	1041180000	-	-
			1		WDK 2.5N ●	1041600000	1041680000	1041620000	1084000000
			2	Disconnect	DLD 2.5 DB	1784180000	6269250000	-	1784210000
			1		WTR 2.5 ●	1855610000	8731640000	-	1050000000
	4	2	2	Fuse (5x20)	WTR 2.5 STB2.3 ●●	1855620000	8731660000	-	-
			1		WDTR 2.5	2456000000	2456010000	-	-
			1	Feed Through	WTR 2.5/SI ●	1763940000	-	-	-
			1		WDU 4 ●●	1020100000	1020180000	1010100000	1050000000
			1	Disconnect	WTR 4 ●	7910180000	7910190000	-	-
			1		WTR 4 STB ●●	7910210000	7910220000	-	-
			1	Fuse (5x20)	WFS 4 ●	2561900000	-	-	-
			1		WSI 4	1886580000	-	-	-
			1	Feed Through	W2C 4 FS BK STB ●●	2892930000	-	-	2894230000
			2		WDK 4N ●	1041900000	1041980000	1041920000	1084000000
	6	2	1	Fuse (5x20) + Feed Through	W2T 4 FS-FT BK STB ●●	2894000000	-	-	2894260000
			1		WDU 6 ●	1020200000	1020280000	1010200000	1050000000
			1	Feed Through	WSI 6	1011000000	1011080000	-	-
			1		WSI 6/LD 10-36V DC/AC	1011300000	-	-	-
			1	Feed Through	WDU 10 ●	1020300000	1020380000	1010300000	1050100000
			1		WDU 16 ●	1020400000	1020480000	1010400000	-
			1		WDU 35 ●	1020500000	1020580000	1010500000	-
			1		WDU 70/95	1024600000	-	-	-
			1		WDU 120/150	1024500000	-	-	-
			1		WDU 240	1802780000	-	-	-
			1		WDU 240	1802780000	-	-	-

- With test socket
- Supports WQV cross connect
- Supports ZQV cross connect

Series / family	mm ²	Connections	Stud Thread	Application	Description	Part Number
WFF Stud terminal	35	2	M6	Stud terminal with protective covers	WFF 35/AH	1029300000
	70		M8		WFF 70/AH	1029400000
	120		M10		WFF 120/AH	1029500000
	185		M12		WFF 185/AH	1029600000
	300		M16		WFF 300/AH	1029700000

Series / family	mm ²	Colour	2-pole	3-pole	4-pole	5-pole	10-pole	20-pole	50-pole
ZQV Cross-connectors	2.5	Orange	1527540000	1527570000	1527590000	1527620000	1527690000	1527720000	1527730000
		Red	2108470000	2108690000	2108700000	2108710000	2108910000	2108920000	2109000000
		Blue	1527740000	1527770000	1527780000	1527790000	1527880000	1527890000	1527920000
	4	Orange	1527930000	1527940000	1527970000	1527980000	1528090000	2883800000	1528130000
		Red	2460450000	2460810000	2460800000	2460790000	2460740000	2810860000	2460730000
		Blue	1528040000	1528080000	1528120000	1528140000	1528230000	2810850000	1528240000


Series / family	mm ²	Colour	2-pole	3-pole	4-pole	5-pole	10-pole	20-pole	50-pole
WQV Cross-connectors	2.5	Yellow	1053660000	1053760000	1053860000	1053960000	1054460000	1577570000	-
	4		1051960000	1054560000	1054660000	1057860000	1052060000	-	-
	6		1052360000	1054760000	1054860000	1062660000	1052260000	-	-
	10		1052560000	1054960000	1055060000	2091130000	1052460000	-	-
	16		1053260000	1055160000	1055260000	-	1053360000	-	-
	35		1053060000	1055360000	1055460000	-	1053160000	-	-

Series / family	Matching Terminal	Description	Part Number
Partition Plate	WDU 2.5, WTR 2.5, WDU 4, WTR 4, WDU 6, WSI 6, WDU 10	WAP 16+35 WTW 2.5-10	1050100000

Tension Clamp Technology (Z-Series)


Build with the best with Weidmüller's Klippon Connect range.

It's our unwavering commitment to quality that has made Weidmüller the name synonymous with terminals in Australia & New Zealand for over 50 years.



Series / family				mm ²	Connections per level	Levels	Application	Description	Standard	Blue	Earth	End Plate
Z-Series Tension Clamp			2.5	2	1	Feed Through	ZDU 2.5	1608510000	1608520000	1608640000	1608740000	
							ZDU 2.5-2 ●	1772060000	1772070000	1706090000	1706110000	
	3	2		ZDK 2.5	1674300000		1678630000	1690000000	1674730000			
				ZDK 2.5-2 ●	1790990000		-	-	1791050000			
	4	1		ZDU 2.5/3AN	1608540000		1608550000	1608650000	1608770000			
				ZDU 2.4-2/3AN ●	1706010000		-	-	1706110000			
	2	Disconnect		ZDU 2.5/4AN	1608570000	1608580000	1608660000	1608800000				
				ZTR 2.5	1831280000	8731710000	-	1608740000				
	2			ZTR 2.5-2 ●	1779010000	-	-	1706110000				
		ZDTR 2.5		1745400000	1798330000	-	1745420000					
				2	1	Fuse (5x20)	ZSI 2.5	1616400000	-	-	1610840000	
							ZDU 4	1632050000	1632060000	1632080000	1632090000	
	3	Feed Through		ZDU 4-2/2AN ●		1770370000	-	-	1770400000			
				ZDU 4/3AN		7904180000	-	7904170000	7940410000			
	ZDU 4-2/3AN ●			1770360000		-	-	1770400000				
	ZDU 6			1608620000		-	1608670000	1608830000				
	ZDU 10			1746750000		-	1746770000	1748660000				
	ZDU 16			1745230000		-	1745250000	1745150000				
				6	2	ZDU 35	1739620000	-	1739650000	-		
10												
		16	2									
				35								

● Compact roof style

Series / family		mm ²	Colour	2-pole	3-pole	4-pole	5-pole	10-pole	20-pole	50-pole
ZQV Cross- connectors	      	1.5	Orange	1985410000	1985480000	1985490000	1985500000	1985580000	1985600000	1985620000
			Red	1985650000	1985670000	1985690000	1985710000	1985800000	1985810000	1985590000
			Blue	1985530000	1985550000	1985570000	1985590000	1985680000	1985700000	1985720000
		2.5	Orange	1527540000	1527570000	1527590000	1527620000	1527690000	1527720000	1527730000
			Red	2108470000	2108690000	2108700000	2108710000	2108910000	2108920000	2109000000
			Blue	1527740000	1527770000	1527780000	1527790000	1527880000	1527890000	1527920000
		4	Orange	1527930000	1527940000	1527970000	1527980000	1528090000	2883800000	1528130000
			Red	2460450000	2460810000	2460800000	2460790000	2460740000	2810860000	2460730000
			Blue	1528040000	1528080000	1528120000	1528140000	1528230000	2810850000	1528240000
		6	Orange	1985740000	1985760000	1985780000		2733970000		
		10		2497250000						
		16		2497290000						
		35		2634950000						

Terminal Accessories

Build with the best with Weidmüller's Klippon Connect range.

It's our unwavering commitment to quality that has made Weidmüller the name synonymous with terminals in Australia for over 50 years.



Series / family		Size	Type	Height	Material	Length	Description	Part Number	
DIN Rail		TS 15	Slotted	5.5mm	Steel, zinc plated, passivated	2m	TS 15X5/LL 2M/ST/ZN	0117500000	
		TS 32	No Slot	15mm			TS 32X15 2M/ST/ZN	0122800000	
			Slotted				TS 32X15/LL 2M/ST/ZN	0514400000	
			No Slot				Stainless steel	TS 32X15 2M/CRN	0293220000
		TS 35	No Slot	7.5mm			Aluminium	TS 32X15 2M/AL/BK	0169300000
					Steel, zinc plated, passivated		TS 35X7.5 2M/ST/ZN	0383400000	
					Aluminium		TS 35X7.5 2M/AL/BK	0330800000	
			Slotted	15mm	Stainless steel		TS 35X7.5 2M/CRN	1747350000	
					Steel, zinc plated, passivated		TS 35X7.5/LL 2M/ST/ZN	0514500000	
							TS 35X7.5/LL/6 2M/ST/ZN	0514570000	
							No Slot	PVC	TS 35X15 2M/ST/ZN
					TS 35X15/6X18 2M/ST/ZN				1805980000
					TS 35X15/LL 2M/ST/ZN				0236500000
								TSK 35X15 2M PVC/GR	0514300000

Series / family	Size	Type	Height	Material	Description	Part Number
DIN Rail End Cap	TS 35	7.5mm	7.5mm	Polypropylene	TS END CAP 35X7.5	1283470000
		15mm	15mm		TS END CAP 35X15	1283480000

Series / family			Terminal Series	Application	Description	Standard	Black
End Bracket			A	End Bracket Screw Clamp	AEB 35 SC/1	1991920000	2475310000
	AEB 35 SC/1	WEW 35/1	W		WEW 35/1	1059000000	1162600000
					WEW 35/2	1061200000	1061210000
	WEW 35/2	AEB 35	A	AEB 35 SCL/1 V0	2661280000	2661300000	
			Z	ZEW 35	9540000000	-	
				ZEW 35/2	8630740000	1162610000	

Series / family	Size	Rated Current	Characteristics	Description	Part Number
Fuse cartridge	5 x 20	0.1A	Fast Blow 1.5kA breaking capacity	G 20/0.10A/F	0430300000
		0.2A		G 20/0.20A/F	0430400000
		0.25A		G 20/0.25A/F	0430500000
		0.5A		G 20/0.50A/F	0430600000
		0.63A		G 20/0.63A/F	0430900000
		1A		G 20/1.00A/F	0430700000
		1.6A		G 20/1.60A/F	0430800000
		2A		G 20/2.00A/F	0430900000
		2.5A		G 20/2.50A/F	0431000000
		3.15A		G 20/3.15A/F	0431100000
		4A		G 20/4.00A/F	0431200000
		5A		G 20/5.00A/F	0431300000
		6.3A		G 20/6.30A/F	0431400000

Series / family	Type	Description	Part Number
Fuse Holder	Fuse holder	ZST 1	1269070000

Series / family	Width	Application	Description	Part Number
Tag Holder	7.2mm	Suits WEW 35/2, ZEW 35, AEB 35 SC/1	EM 8/30	1806120000
	9.5mm	Group marker carrier, DIN mount	SCHT 5 S	1631930000
	19.5mm		SCHT 5	0292460000

Power Supplies

Reliable production requires a reliable power source. We have solutions to suit your simplest control board to your most complex and critical plant operations.



Series / family		Voltage	Output	Description	Single Phase	Three Phase
 PRObas	Entry level, for general industrial loads	5V DC	6A	PRO BAS 30W 5V 6A	2838400000	-
		12V DC	2.6A	PRO BAS 30W 12V 2.6A	2838510000	-
			5A	PRO BAS 60W 12V 5A	2838420000	-
		24V DC	10A	PRO BAS 120W 12V 10A	2838450000	-
			1.3A	PRO BAS 30W 24V 1.3A	2838500000	-
			2.5A	PRO BAS 60W 24V 2.5A	2838410000	-
			5A	PRO BAS 120W 24V 5A	2838440000	-
			10A	PRO BAS 240W 24V 10A	2838460000	-
			20A	PRO BAS 480W 24V 20A	2838480000	-
		48V DC	5A	PRO BAS 240W 48V 5A	2838470000	-
			10A	PRO BAS 480W 48V 10A	2838490000	-
 PROeco	Standard range, wide range options for single and 3-phase	12V	6A	PRO ECO 72W 12V 6A	1469570000	-
			10A	PRO ECO 120W 12V 10A	1469580000	-
		24V	3A	PRO ECO 72W 24V 3A	1469470000	-
			5A	PRO ECO 120W 24V 5A	1469480000	-
				PRO ECO3 120W 24V 5A	-	1469530000
			10A	PRO ECO 240W 24V 10A	1469490000	-
				PRO ECO3 240W 24V 10A	-	1469540000
			20A	PRO ECO 480W 24V 20A	1469510000	-
				PRO ECO3 480W 24V 20A	-	1469550000
			40A	PRO ECO 960W 24V 40A	1469520000	-
				PRO ECO3 960W 24V 40A	-	1469560000
		48V	5A	PRO ECO 240W 48V 5A	1469590000	-
			10A	PRO ECO 480W 48V 10A	1469610000	-
 PROmax	Mid Level, 300% top boost for demanding loads	5V	14A	PRO MAX 70W 5V 14A	1478210000	-
		12V	6A	PRO MAX 72W 12V 6A	1478220000	-
			10A	PRO MAX 120W 12V 10A	1478230000	-
		24V	3A	PRO MAX 72W 24V 3A	1478100000	-
			5A	PRO MAX 120W 24V 5A	1478110000	-
				PRO MAX3 120W 24V 5A	-	1478170000
			7.5A	PRO MAX 180W 24V 7.5A	1478120000	-
			10A	PRO MAX 240W 24V 10A	1478130000	-
				PRO MAX3 240W 24V 10A	-	1478180000
			20A	PRO MAX 480W 24V 20A	1478140000	-
				PRO MAX3 480W 24V 20A	-	1478190000
			40A	PRO MAX 960W 24V 40A	1478150000	-
				PRO MAX3 960W 24V 40A	-	1478200000
		48V	5A	PRO MAX 240W 48V 5A	1478240000	-
			10A	PRO MAX 480W 48V 10A	1478250000	-
			20A	PRO MAX 960W 48V 20A	1478270000	-
				PRO MAX3 960W 48V 20A	-	-
 PROtop	Top Level, 600% top boost, High Reliability, for heavy loads and circuit breaker tripping Built in ORing MOSFET	12V	10A	PRO TOP1 120W 12V 10A	2466910000	-
				PRO TOP1 120W 12V 10A EX ●	2467020000	-
		24V	3A	PRO TOP1 72W 24V 3A	2466850000	-
				PRO TOP1 72W 24V 3A CO ●	2466970000	-
			5A	PRO TOP1 120W 24V 5A	2466870000	-
				PRO TOP3 120W 24V 5A	-	2467060000
				PRO TOP1 120W 24V 5A EX ●	2466980000	-
			10A	PRO TOP3 120W 24V 5A CO ●	-	2467070000
				PRO TOP1 240W 24V 10A	2466880000	-
				PRO TOP3 240W 24V 10A	-	2467080000
			20A	PRO TOP1 240W 24V 10A EX ●	2466990000	-
				PRO TOP3 240W 24V 10A CO ●	-	2467090000
				PRO TOP1 480W 24V 20A	2466890000	-
			40A	PRO TOP3 480W 24V 20A	-	2467100000
				PRO TOP1 480W 24V 20A EX ●	2467000000	-
				PRO TOP3 480W 24V 20A CO ●	-	2467110000
		48V	10A	PRO TOP1 960W 24V 40A	2466900000	-
				PRO TOP3 960W 24V 40A	-	2467120000
				PRO TOP1 960W 24V 40A EX ●	2467010000	-
			20A	PRO TOP3 960W 24V 40A CO ●	-	2467130000
				PRO TOP1 480W 48V 10A	2467030000	-
				PRO TOP3 480W 48V 10A	-	2467150000
				PRO TOP1 480W 48V 10A EX ●	2467040000	-
				PRO TOP3 480W 48V 10A CO ●	-	2467160000
				PRO TOP1 960W 48V 20A	2466920000	-
				PRO TOP3 960W 48V 20A	-	2467170000
				PRO TOP1 960W 48V 20A CO ●	2467050000	-
				PRO TOP3 960W 48V 20A CO ●	-	2467180000

- Extended performance, IECEx zone 2, conformal coated
- Extended performance, conformal coated
- ➡ Performance

DC UPS & DC/DC Converter

Flexible, reliable and safe in every environment. Our DC-UPS systems, buffer modules, redundancy modules and DC/DC converters improve the reliability and flexibility of your systems



Series / family	Nominal Voltage	Redundancy Type	Technology	Voltage Drop	Description	Part Number
Redundancy Modules  PRO DM10 PRO RM10 PRO RM40	0-60 VDC	2 x 10A	Diode	Vin - 0.7V	PRO DM 10	2486070000
		2 x 20A			PRO DM 20	2486080000
	12 / 24 VDC	2 x 10A	MOSFET with Active Load Sharing	< Vin - 0.2V	PRO RM 10	2486090000
		2 x 20A			PRO RM 20	2486100000
		2 x 40A			PRO RM 40	2486110000

DC Buffering

1. If your duration is short (<5s), consider using a buffer module, otherwise consider a DC UPS.
2. Determine your maximum load current and maximum buffering time.
3. Use the below battery selection graph to choose the most suitable battery to go with your DC UPS.

Series / family	Nominal Voltage	Rated Current	Buffer Duration	Technology	Description	Part Number
DC UPS	24V DC	20A	-	VRLA charger	DC UPS 24V 10/20A	1370050010
		40A			DC UPS 24V 40A	1370040010
UPS Battery  DC UPS Controller PRO DC Buffer	24V DC	15A	6 min @ 5A	VRLA AGM	DURA ECO LA-BAT 24V 1.2AH	2789890000
		25A	10 min @ 10A		DURA ECO LA-BAT 24V 3.4AH	2789900000
		50A	23 min @ 10A		DURA ECO LA-BAT 24V 7AH	2789910000
			50 min @ 10A		DURA ECO LA-BAT 24V 12AH	2789920000
			72 min @ 10A		DURA ECO LA-BAT 24V 17AH	2789930000
Buffer Module	24V DC	20A	320ms @ 20A	Capacitor	PRO DC BUFFER 24V 20A	2786240000
		40A	230ms @ 40A		PRO DC BUFFER 24V 40A	2786250000

Series / family	Nominal Input	Min/Max Voltage Input	Nominal Output	Min/Max Voltage Output	Rated Current	Description	Part Number
DC/DC Converter  PRO DCDC 10A PRO TOPDC 10A	12 VDC	9-18V DC	12V DC	5-15V DC	8A	PRO DCDC 96W 12V/12V 8A	2869000000
			24V DC	22-29V DC	5A	PRO DCDC 120W 12V/24V 5A	2869030000
	24V DC	18-34V DC	12V DC	5-15V DC	8A	PRO DCDC 96W 24V/12V 8A	2869010000
					5A	PRO DCDC 120W 24V 5A	2001800000
			24V DC	22-29V DC	10A	PRO DCDC 240W 24V 10A	2001810000
					20A	PRO DCDC 480W 24V 20A	2001820000
					5A	PRO DCDC 240W 24V/48V 5A	2869050000
					8A	PRO DCDC 96W 48V/12V 8A	2869020000
	48V DC	28-58V DC	12V DC	5-15V DC	8A	PRO DCDC 120W 48V/24V 5A	2869040000
			24V DC	22-29V DC	5A	PRO DCDC 120W 48V/24V 5A	2869040000
			48V DC	29-56V DC	5A	PRO DCDC 240W 48V/48V 5A	2869060000
	24V DC	14-31V DC	24V DC	22-29V DC	5A	PRO TOPDC 24V/24V 5A	2627650000
					10A	PRO TOPDC 24V/24V 10A	2627640000
			48V DC	45-56V	20A	PRO TOPDC 24V/24V 20A	2627630000
					10A	PRO TOPDC 24V/48V 10A	2627660000


Series / family		Voltage	Output	Phase	Description	Part Number	
PRO INSTA	 Compact, for small loads and light control	5V	6A	1	PRO INSTA 30W 5V 6A	2580210000	
		12V	2.6A		PRO INSTA 30W 12V 2.6A	2580220000	
			5A		PRO INSTA 60W 12V 5A	2580240000	
		24V	0.7A		PRO INSTA 16W 24V 0.7A	2580180000	
			1.3A		PRO INSTA 30W 24V 1.3A	2580190000	
			2.5A		PRO INSTA 60W 24V 2.5A	2580230000	
			4A		PRO INSTA 96W 24V 4A	2580260000	
		48V	2A		PRO INSTA 96W 48V 2A	2580270000	

Accessories

Series / family	Network	Voltage	N-E Combined (MEN)	I _{max} (8/20us)	Application	Fault Contact	Description	Part Number
Accessories 	1-phase	240 VAC	-	20kA	Power supply surge protection	Yes	VPU AC II+III 1+1 R 275/20 S	2907940000
	3-phase						VPU AC II+III 3 R 275/20 S	2907880000

Electronic Fuse

maxGUARD. The modular electronic fuse. Protect your control voltage distribution with the flexible and modular maxGUARD electronic fuse terminal range.



Series / family	Function	Description	Part Number
maxGUARD Feed in modules  AMG FIM	Feed in module basic. 40A max.	AMG FIM-0	2081870000
	Feed in module with remote reset and alarm. 40A max	AMG FIM-C	2081880000

Series / family	Function	Description	Part Number
maxGUARD function modules   AMG CM AMG AM	Optional control module, with remote reset, alarm, >90% pre-warning alarm, ON/OFF. Use with AMG FIM-0	AMG CM	2081900000
	Optional alarm module with relay contacts for trip alarm & >90% pre-warning	AMG AM	2081890000

Series / family	Nominal Voltage	Rated Current	Adjustable	Description	Part Number
maxGUARD Electronic fuse modules   AMG ELM 1-6A AMG ELM 10-18A	24V DC	1A	Fixed	AMG ELM-1F	2080420000
		2A		AMG ELM-2F	2080480000
		4A		AMG ELM-4F	2080490000
		6A		AMG ELM-6F	2080500000
		8A		AMG ELM-8F	2080600000
		10A		AMG ELM-10F	2080650000
		0.1A, 0.2A, 0.5A, 0.8A, 1A	Yes	AMG ELM-1 LIM CL2 EX	2838530000
		1A, 2A, 3A, 4A, 6A		AMG ELM-6	2080360000
		4A, 6A, 8A, 10A, 12A		AMG ELM-12	2080410000
		10A, 12A, 14A, 16A, 18A		AMG ELM-18	2859800000
		1A, 2A, 3A, 4A, 6A		AMG ELM-6D CO	2082440000
		4A, 6A, 8A, 10A		AMG ELM-10D CO	2082470000



Series / family	Poles	Description	Red	Blue	Orange
Cross Connect   	10	ZQV 4N/10	2460740000	1528230000	1528090000
	50	ZQV 4N/50	2460730000	1528240000	1528130000

maxGUARD modular Electronic Fuse

- Select feed in module depending if you need remote reset or not.
- Select your required electronic fuse cards depending on your loads. Keep in mind not to exceed 40A max.
- Select your cross connects for the positive, negative and communication channels. If the total current is >20A, you will need to use 2 cross connects each for the positive and negative channels.

Notes:

- Maximum limit of 25 fuse modules on a single AMG FIM-C or AMG CM module.
- EX, conformal coated fuses and additional accessories are available from the full catalogue.



Industrial Ethernet Switches

Stable process control requires a stable communication base. Weidmüller's range of industrial ethernet switches provide the perfect link for data communication between Ethernet enabled devices in industrial automation. We offer a wide range of products to suit requirements in industrial networking.



Series / family			RJ45 Ports	Fibre Ports	SFP Ports	Speed	Application	Power	Description	Part Number					
Ecoline Unmanaged Switch	 		5	-	-	10/100	General Networking Applications	12-48VDC, 24VAC redundant	IE-SW-EL05-5TX	2682130000					
			8	-	-				IE-SW-EL08-8TX	2682140000					
			5	-	-				IE-SW-EL05-5GT	2682210000					
			4	-	1				IE-SW-EL05-4GT-1GESFP	2682220000					
	 		8	-	-	Gigabit	Compact Width	12-48VDC redundant	IE-SW-EL08-8GT	2682230000					
			8	-	-				IE-SW-EL08-8GT-MINI	2705000000					
			6	2 x SC MM	-				10/100+ 2xGigabit	General Networking Applications	12-48VDC	IE-SW-EL08-6TX-2SC	2682170000		
			6	2 x SC SM	-							IE-SW-EL08-6TX-2SCS	2682180000		
	 		16	-	-	10/100+ 2xGigabit	12-48VDC redundant	IE-SW-EL16-16TX				2682150000			
			14	-	2			IE-SW-EL16-14TX-2FESFP				2682160000			
			18	-	2			IE-SW-EL18-16TX-2GC	2682200000						
			24	-	-			IE-SW-EL24-24TX	2682190000						
Ecoline PoE Switch	 		4	2 x SC MM	-	10/100	PoE 802.3af/at	12-48VDC redundant	IE-SW-EL6-4PoE-2SC	2682390000					
			8	-	-				IE-SW-EL8-8PoE	2682380000					
			8	-	-				IE-SW-EL8-8GTPoE	2682400000					
			8	-	2				IE-SW-EL10-8GTPoE-2GESFP	2682410000					
	 		2	-	-	Gigabit	Gigabit PoE Injector 802.3af/at 60W Budget	12-48VDC redundant	IE-INJ-EL02-2GTPOE	2682440000					
		AdvancedLine Managed Switch	 		5				-	-	10/100	Lite Managed, Economical Ring Switch	12-48VDC redundant	IE-SW-AL05LM-5TX	2682250000
					4				2 x SC MM	-				IE-SW-AL06LM-4TX-2SC	2682260000
					4				2 x SC SM	-				IE-SW-AL06LM-4TX-2SCS	2682270000
				8	-	-	IE-SW-AL08M-8TX	2682280000							
	 			16	-	-	10/100+ 2xGigabit	General Managed Networking	IE-SW-AL16M-16TX	2682310000					
				24	-	-			IE-SW-AL24M-24TX	2682320000					
				8	-	-			IE-SW-AL08M-6TX-2GT	2682290000					
			10	-	2	IE-SW-AL10M-8TX-2GC			2740420000						
 		18	-	2	10/100+ 2xGigabit Combo		IE-SW-AL18M-16TX-2GC	2682330000							
		8	-	-			IE-SW-AL8M-8GT	2682350000							
		8	-	4			IE-SW-AL12M-8GT-4GESFP	2682340000							
		12	-	2			IE-SW-AL14M-12GT-2GESFP	2682360000							
AdvancedLine Managed PoE Switch	 		16	-	8	Gigabit	Profinet & Ethernet/IP Protocol Support	12-48VDC redundant	IE-SW-AL24M-16GT-8GESFP	2682370000					
			8	-	-				IE-SW-AL8M-8GT	2682350000					
			8	-	4				IE-SW-AL12M-8GT-4GESFP	2682340000					
		12	-	2	IE-SW-AL14M-12GT-2GESFP	2682360000									
		4	-	2	Gigabit	Gigabit PoE 802.3af/at 120W budget	IE-SW-AL06M-4GTPOE-2GESFP		2682430000						
	8	-	-	IE-SW-AL08M-8GTPOE			2682420000								

Series / family	Speed	Mode	Distance	Description	Part Number
SFP Modules		Multimode	2km	IE-SFP-1FE-MM-2	2682450000
			30km	IE-SFP-1FE-SM-30	2682460000
		Singlemode	60km	IE-SFP-1FE-SM-60	2682470000
			0.5km	IE-SFP-1GE-MM-05	2682480000
	Gigabit	Multimode	2km	IE-SFP-1GE-MM-2	2682490000
			10km	IE-SFP-1GE-SM-10	2682500000
		Singlemode	40km	IE-SFP-1GE-SM-40	2682510000
			40km	IE-SFP-1GE-SM-40	2682510000

Series / family		Network	Voltage	Class	I _{max} (8/20us)	Application	Fault Contact	Description	Part Number
Accessories		Data	48 VDC	-	10kA	Cat6A cabling, suitable for PoE devices to 802.3at/af/bt	No	VDATA CAT6	1348590000

Rackmount switches, routers and IOT

Stable process control requires a stable communication base. Managed switches supporting energy industry requirements of 61850-3



Series / family		RJ45 Ports	SFP Ports	Speed	Application	Power	Description	Part Number
61850-3 DIN Mount Managed Switch		10	3	10/100+ 3xGigabit Combo	IEC 61850-3 Substation	12 / 24 / 48 VDC	IE-SW-SL10M-7TX-3GC-LV	2778960000
						110/220 VDC 110/230 VAC	IE-SW-SL10M-7TX-3GC-HV	2778950000
		8	12	Gigabit		12 / 24 / 48 VDC	IE-SW-SL20M-8GT-12GESFP-LV	2778980000
						110/220 VDC 110/230 VAC	IE-SW-SL20M-8GT-12GESFP-HV	2778970000
61850-3 19" Rackmount Managed Switch		24	2	10/100+ 2xGigabit Combo	IEC 61850-3 Substation	24 / 28 VDC	IE-SW-SL26M-24TX-2GC-LV	2779000000
						110/220 VDC 110/230 VAC	IE-SW-SL26M-24TX-2GC-HV	2778990000

Series / family	Total Slots	Application	Power	Description	Part Number
61850-3 19" Modular Rackmount Managed Switch 	4 (M1, M2, M3, M4)	IEC 61850-3 Substation	24 / 28 VDC	IE-SW-SL28M-LV	2779020000
			110/220 VDC 110/230 VAC	IE-SW-SL28M-HV	2779010000
61850-3 19" Modular Rackmount Layer 3 Managed Switch 	4 (M1, M2, M3, M4)	IEC 61850-3 Substation, routing	24 / 28 VDC	IE-SW-L3-SL28M-LV	2875590000
			110/220 VDC 110/230 VAC	IE-SW-L3-SL28M-HV	2875580000

Series / family		Port Type	Supported Slots	Application	Description	Part Number
Modular Plug-in modules		8 x 10/100/1000 BaseT(X) RJ45	M1, M2, M3	To suit IE-SW-SL28M series	IE-SWM-SL08-8GT	2779140000
		8 x 100/1000Base SFP			IE-SWM-SL08-8GESFP	2779150000
		4 x 100BaseFX SC			IE-SWM-SL04-4SC	2779170000
		4 x 100BaseFX SCS			IE-SWM-SL04-4SCS	2779160000
		4 x 100BaseFX ST			IE-SWM-SL04-4ST	2779190000
		4 x 100BaseFX STS			IE-SWM-SL04-4STS	2779180000
		4 x 1000Base SFP	M4		IE-SWM-SL04-4GESFP	2779200000
		2 x 10GBaseSFP+			IE-SWM-SL02-2GESFP+	2779210000
		4 x 10GBaseSFP+			IE-SWM-SL04-4GESFP+	2779220000


Series / family	Ports	Function	Application	Power	Description	Part Number
Security Router 	2 x RJ45 + 1 x RS232/422/485 + 2DI + 1DO	Wifi 802.11b/g/n	Wifi Security Router	12 / 24 / 48 VDC, PoE	IE-SR-2TX-WL	2682590000
		Wifi 802.11b/g/n, 4G LTE	Wifi 4G Security Router		IE-SR-2TX-WL-4G-EU	2682560000
	2 x RJ45 + 1 x RS232/422/485 + 1 USB + 2DI + 1DO	LAN/WAN IOT Gateway	Programmable, IOT	24 VDC	IOT-GW30	2682620000
		4G LTE/LAN/WAN IOT Gateway	Programmable, IOT sensor to cloud		IOT-GW30-4G-NA	2682640000

Series / family	Ports	Application	Power	Description	Part Number
Serial to Ethernet Converter 	2 x RJ45 + 1 x RS232/422/485	Serial to Ethernet Conversion. Modbus RTU to Modbus TCP conversion.	12 / 24 / 48 VDC	IE-CS-MBGW-2TX-1COM	2682600000

Series / family	Ports	Supported Protocols	Application	Power	Description	Part Number
Universal Gateway Protocol Converter 	2 x RJ45 + 2 x RS232/RS485	Ethernet/IP (client), Modbus TCP (client/server), Modbus RTU (client/server), Modbus ASCII (client/server), S7comm (ISOTCP client),	Simultaneously converter between multiple protocols, enables communication between different fieldbuses and PLCs offered by Rockwell, Siemens, Schneider and more	12-24V DC	IE-UGW-2TX-2RS232/485	7940124932
	2 x RJ45 + 4 x RS232/RS485				IE-UGW-2TX-4RS232/485	7940124933

Industrial Ethernet Connectivity


Solutions for connection of Ethernet cabling. Choose from a large number of interfacing options for RJ45, Fibre Optic, USB and more.



Series / family				
DIN rail outlets				
	Type	RJ45-RJ45 Coupling	RJ45-RJ45 Coupling Angled	RJ45 Field Wireable
	Description	IE-TO-RJ45-C	IE-XM-RJ45/RJ45	IE-TO-RJ45-FJ-A
	Part Number	8946920000	8879050000	8946930000
	Type	RJ45 Field Wireable Angled	LC-LC Multimode	LC-LC Singlemode
	Description	IE-XM-RJ45/IDC	IE-TO-LCD-MM	IE-TO-LCD-SM
	Part Number	8808360000	8947010000	8947020000
	Type	ST-ST Fibre	SC-SC Multimode	SC-SC Singlemode
	Description	IE-XM-ST/ST	IE-TO-SCD-MM	IE-TO-SCD-SM
	Part Number	8808340000	8946970000	8946980000
RJ45 plugs				
	Type	RJ45 Coupling		
	Description	IE-TO-RJ45-C-LP		
	Part Number	2812440000		
RJ45 plugs				
	Type	Field wireable Plug	Field wireable Plug with Cable Gland	Field wireable Plug 90°
	Description	IE-PS-RJ45-FH-180-A-1.6	IE-PS-RJ45-FH-180-A-1.6-CG	IE-PS-RJ45-FH-90-A-1.6
	Part Number	1992820000	2703390000	1992870000
FrontCom Micro Service Interface				
	Type	RJ45-RJ45 Coupling	RJ45 Field wireable	USB Type A Coupling
	Description	IE-FCM-RJ45-C	IE-FCM-RJ45-FJ-A	IE-FCM-USB-A
	Part Number	1018790000	1018810000	1018840000
				-
	Type	USB Type A to Type B	USB 3.0 Coupling	-
IP67 Connectivity - Bayonet Metal				
	Type	Field wireable Plug	RJ45-RJ45 Coupling bulkhead	Field wireable bulkhead
	Description	IE-PS-V01M-RJ45-FH-BP	IE-BS-V01M-RJ45-C	IE-BS-V01M-RJ45-FJ-A
	Part Number	1963130000	1963470000	1963480000
IP67 Connectivity - Bayonet Plastic				
	Type	Field wireable Plug	RJ45-RJ45 Coupling bulkhead	Field wireable bulkhead
	Description	IE-PS-V01P-RJ45-FH	IE-BS-V01P-RJ45-C	IE-BS-V01P-RJ45-FJ-A
	Part Number	1012490000	1012370000	1012380000


Industrial Ethernet Connectivity

Solutions for connection of Ethernet cabling. Choose from a large number of interfacing options for RJ45, Fibre Optic, USB and more.



Series / family				
D-Coded M12 Connectors				
	Type	Field wireable Plug Screw	Field wireable Plug PUSH-IN	M12 D-code female to RJ45 Straight
	Description	SAISM-4/8S-M12-4P D-COD	SAISP-M-4D-4/8-M12	IE-M12-ADAP 2
	Part Number	1892120000	2681680000	8901620000
				
	Type	Field wireable Plug 90° Screw	Field wireable Plug 90° PUSH-IN	M12 D-code male to RJ45 Straight
X-Coded M12 Connectors	Description	SAISW-4/8S-M12-4P D-COD	SAISWP-M-4D-4/8-M12	IE-AD-M12DRJ45-MF-180
	Part Number	1160550000	2681690000	1514970000
				-
	Type	Field wireable Plug	M12 X-code to RJ45 Straight	-
	Description	IE-PS-M12X-P-FH	IE-AD-M12XRJ45-180	-
	Part Number	1324020000	1400620000	-

Series / family		Type	Grey	Blue	Black	Green	Red	Magenta	Yellow
RJ45 Patch Cabling		0.5 m	1165940005	1165900005	1251610005	1251590005	1166030005	1201270005	1251580005
		1 m	1165940010	1165900010	1251610010	1251590010	1166030010	1201270010	1251580010
		1.5 m	1165940015	1165900015	1251610015	1251590015	1166030015	1201270015	1251580015
		2 m	1165940020	1165900020	1251610020	1251590020	1166030020	1201270020	1251580020
		3 m	1165940030	1165900030	1251610030	1251590030	1166030030	1201270030	1251580030
		5 m	1165940050	1165900050	1251610050	1251590050	1166030050	1201270050	1251580050
		10 m	1165940100	1165900100	1251610100	1251590100	1166030100	1201270100	1251580100

Series / family		Plastic Lid – Cabinet Key Lock	Metal Lid – Cabinet Key Lock
			
	Type	1x 10A GPO + 1xRJ45 + 1xUSB + Touch Protection	1x 10A GPO + 1xRJ45 + 1xUSB + Touch Protection
	Description	IE-FC-SET-IPAUS01-CAB-P	IE-FC-SET-IPAUS01-CAB-M
	Part Number	7940127809	7940127810
IP65 Service Interface Kits			

Remote IO & Controllers

Meet the most innovative I/O system on the market, u-remote. u-remote takes the most user-friendly I/O concept and combines this with high-performance hardware in a compact size.



Series / family	Description	Part Number
Fieldbus Coupler	 UR20-FBC-EIP	1334920000
	UR20-FBC-EIP-V2 ●	1550550000
	 UR20-FBC-MOD-TCP-V2	2476450000
	 UR20-FBC-PN-HRT-V2	2566380000
	 UR20-FBC-PB-DP-V2	2614380000
	 UR20-FBC-EC	1334910000

● DLR + PRP Redundancy supported

- Built-in webserver for easy configuration
- Dual RJ45 ports (Ethernet Models)
- Separated dual 10A Input/output power bus
- Integration with most major PLC Vendors, Allen Bradley, Siemens, Schneider

Series / family	Type	Channels	Function	Description	Part Number
I/O Slice	Digital Input	16	1-wire	UR20-16DI-P	1315200000
			1-wire, PLC ribbon interface	UR20-16DI-P-PLC-INT	1315210000
	Digital Output	8	2-wire	UR20-8DI-P-2W	1315180000
			1-wire	UR20-16DO-P	1315250000
	Digital In/Out	16	1-wire, PLC ribbon interface	UR20-16DO-P-PLC-INT	1315270000
		8	2-wire	UR20-8DO-P	1315240000
	Relay Output	4	Changeover relay	UR20-4RO-CO-255	1315550000
		8	2/3-wire configurable in/out	UR20-8DIO-P-3W-DIAG	2456530000
	Solid State Output	4	Relay output, 250V 6A max	UR20-4RO-CO-255	1315550000
		4	SSR output, 250VAC 1A max	UR20-4RO-SSR-255	1315540000
	Analogue Input	4	4-wire 4-20mA / 0-10V input 16bit	UR20-4AI-UI-16	1315620000
		4	4-wire 4-20mA / 0-10V input 16bit, diagnostic	UR20-4AI-UI-16-DIAG	1315690000
		4	4-wire 4-20mA input 16bit + HART	UR20-4AI-HART-16-DIAG	2617520000
	Analogue Output	4	4-wire 4-20mA / 0-10V output 16bit	UR20-4AO-UI-16	1315680000
		4	4-wire 4-20mA / 0-10V output 16bit, diagnostic	UR20-4AO-UI-16-DIAG	1315730000
Power Feed	Temperature Input	4	4-wire RTD input	UR20-4AI-RTD-DIAG	1315700000
		4	2-wire Thermocouple input	UR20-4AI-TC-DIAG	1315710000
	Load Cell	2	4-wire Load cell input 24bit	UR20-2AI-SG-24-DIAG	1990070000
	Serial	1	RS232,485,422 + Modbus RTU	UR20-1COM-232-485-422-V2	2826800000
	Power Feed	0	Input bus 10A	UR20-PF-I	1334710000
			Output bus 10A	UR20-PF-O	1334740000

*More modules models available on request

Series / family	Software applications	Hardware Specifications	Connections	Expandability	Description	Part Number
Edge & IIoT Controller	 CODESYS ●, Node-RED, Easyconnect, PROCON-Web, u-link, App Hub	Dual core A9, 624 Mhz, 512 Mbyte RAM, 4GB embedded flash, 32GB via microSD, RTC	2 x RJ45, 1 x Micro USB	Yes, with UR20 I/O slices	UC20-WL2000-AC	1334950000
		Dual core A53, 1200 Mhz, 2 GB RAM, 8GB embedded flash, 32GB via microSD, RTC	2 x 1Gbps RJ45, 2 x USB-A, 1 x USB-C		UC20-M3000	2839150000
		Quad core A53, 1200 Mhz, 4 GB RAM, 8GB embedded flash, 32GB via microSD, RTC	4 x 1Gbps RJ45, 2 x USB-A, 1 x USB-C		UC20-M4000	2839160000

● Requires license

Energy Metering

Energy data acquisition with an excellent price-performance ratio.

The practical solution for monitoring basic electrical data of machines and systems.



Series / family		Inputs	Voltage Range (L-N)	Input Type	Accuracy Class	Communication	Mounting	Description	Part Number
Energy Metering		1-phase	176-276V AC	1A/5A CT	Class 1	Modbus RTU RS485, Pulse	DIN mount	EM110-RTU-2P	7760051002
				Direct connect 45A				EM111-RTU-2P	7760051001
		3-phase	138-276V AC	1A/5A CT	Class 0.5			EM120-RTU-2P	7760051004
				Direct connect 100A				EM122-RTU-2P	7760051003
			50-345V AC	1A/5A CT	Class 0.5s	Modbus RTU RS485, Pulse, 4DI, 2DO	Panel mount	EM220-RTU-4DI2DO	7760051005
						Modbus TCP, Modbus RTU RS485, Pulse, 4DI, 2DO		EM220-RTU-4DI2DO-GW	7760051006

Series / family	Primary Current	Secondary Current	Class	Description	Part Number
Current Transformer	60A	5A	1	CMA-31-60-5A-1,25VA-1	2421380000
	75A			CMA-31-75-5A-2,5VA-1	1482040000
	100A			CMA-31-100-5A-2,5VA-1	1482030000
	150A			CMA-31-150-5A-5VA-1	2420960000
	200A			CMA-31-200-5A-5VA-1	2420950000
	250A			CMA-31-250-5A-5VA-1	2420940000
	400A			CMA-31-400-5A-5VA-1	2420920000
	500A			CMA-31-500-5A-5VA-1	2420910000
	600A			CMA-31-600-5A-5VA-1	2420900000
	750A			CMA-31-750-5A-5VA-1	2420890000

Series / family	Input	Output	Accuracy	Application	Description	Part Number
Rogowski Transducer	100-5000A AC (using RCMA-B22 Rogowski Coil)	0-1A AC	<0.5% of measuring range	Rogowski coil transducer, for connection to 1A input energy meter	RCMC-5000-1A-P	2593400000

Series / family	Max Primary Current	Conductor Size	Cable Length	Application	Description	Part Number
Rogowski Coil	5000A AC	70 mm	4.5m	Rogowski coil, large diameter cables	RCMA-B22-D70-4.5	2593340000
		125 mm			RCMA-B22-D125-4.5	2593350000
		175 mm			RCMA-B22-D175-4.5	2593360000

Termseries PLC Relays

Termseries, the all-rounder interposing relay for PLCs and controls. Choose from a wide range of electromechanical relays and solid-state relays in screw or PUSH IN connection.



Series / family		Coil Voltage	Load* Max	Con-tacts	Contact material	Application	Description	Screw	PUSH IN		
Electromechanical Relay		5VDC	6A	1CO	AgNi	General purpose	TRS 5VDC 1CO	1122740000	2614830000		
		12VDC	6A	1CO			TRS 12VDC 1CO	1122750000	2618180000		
			8A	2CO			TRS 12VDC 2CO	1123480000	2618550000		
		24VDC	6A	1CO	AgNi + Gold		Very low current / voltage switching	TRS 24VDC 1CO	1122770000	2618000000	
			8A	2CO				TRS 24VDC 2CO	1123490000	2618400000	
			6A	1CO				AgNi	Actuator switching	TRS 24VDC 1CO AU	1123000000
			8A	2CO	TRS 24VDC 2CO AU	1123730000	2618530000				
			6A	1NO	General purpose	TRS 24VDC ACT	1381900000			2618230000	
			16A	1CO		TRS 24VDC 1CO 16A	1479680000	2618100000			
			6A	1CO		AgSnO	Moderate inrush	TRS 24VDC 1CO AGSNO	1984540000	2618020000	
				16A	1NO			TRS 24VDC 1NO HC	1479780000	2618090000	
				AgSnO + W	Capacitive loads, LED drivers			TRS 24VDC 1NO HCP	1479810000	2617930000	
		24V AC/DC		6A	1CO	AgSnO	General purpose + Test button	TRS 24VDC 1CO AGSNO PB	2855870000	2855800000	
			6A	1CO	AgNi			General purpose	TRS 24VUC 1CO	1122780000	2618220000
			8A	2CO					TRS 24VUC 2CO	1123500000	2618320000
			6A	1CO		AgSnO	General purpose + Test button		TRS 24VUC 1CO AGSNO PB	2855890000	2855810000
			6A	1CO	AgNi + Gold			Very low current / voltage switching	TRS 24VUC 1CO AU	1123010000	2618160000
			8A	2CO					TRS 24VUC 2CO AU	1123740000	2618540000
				24-230V AC/DC		48V AC/DC	6A		AgNi	General purpose	TRS 48VUC 1CO
					8A	2CO	TRS 48VUC 2CO	1123510000			2618520000
					120V AC/DC	6A	1CO	TRS 120VUC 1CO			1122810000
	6A	1CO			TRS 230VUC 1CO	1122820000	2618050000				
	8A	2CO			TRS 230VUC 2CO	1123540000	2618440000				
	230VAC	6A			1CO	AC switching with RC filter	TRS 230VAC RC 1CO	1122840000			2618200000
	6A	1CO			General purpose		TRS 24-230VUC 1CO	2662850000			2663010000
8A	2CO	TRS 24-230VUC 2CO					2662880000	2663040000			
6A	1CO	AgSnO				General purpose + Test button	TRS 24-230VUC 1CO AGSNO ED2 PB	2855930000	2855910000		
Solid State Relay		12VDC	100mA	1NO	Transistor	PLC I/O Interposing	TOS 12VDC 48VDC0.1A	1126930000	2618600000		
		24VDC					2A	MOSFET	High load switching	TOS 24VDC 48VDC0.1A	1126940000
					3.5A	TOS 24VDC 24VDC2A	1127170000			2618720000	
		5A			TOS 24VDC 24VDC3.5A	1127630000	2618700000				
		230V AC/DC	100mA	1NO	Transistor	AC interposing	TOS 24VDC 24VDC5A	1990960000	2618840000		
		24-230V AC/DC					TOS 230VUC 48VDC0.1A	1126990000	2618690000		
		1A AC			TRIAC	TOS 24-230VUC 48VDC0.1A	1127020000	2663070000			
						TOS 24-230VUC 230VAC1A	1127500000	2663090000			
Forcibly Guided Relay		24V AC/DC	6A	2CO	AgNi	Forcibly guided to EN 61810-3 type B	TRS 24VUC 2CO FG	2706290000	2706430000		
Timer Relay		24VDC	6A	1CO	AgSnO	Timer - On Delay, One Shot, Blinker, 0-100s	TRS T 24VDC 1CO M3	2639560000	2639730000		
Compact Relay		24V DC	6A	1NO	AgNi	PLC Interposing, built-in Fuse (5x20)	TRPL 24VDC 1NO F	-	2773930000		
		5VDC					1CO	Compact General Purpose	TRPL 5VDC 1CO	-	2774030000
		24VDC							TRPL 24VDC 1CO	-	2773890000
		24V AC/DC							TRPL 24VUC 1CO	-	2773970000
	12-60V AC/DC	TRPL 12-60VUC 1CO		-		2773770000					
		24-230V AC/DC		1CO		Compact General Purpose	TRPL 24-230VUC 1CO	-	2773860000		
		120V AC					TRPL 120VAC 1CO	-	2773800000		
		230V AC					TRPL 230VAC 1CO	-	2773830000		
Accessories			-		-		-	-	8 x 6mm relays. 10-pole connector	TIA F10 8X1CO	-
	-		-	-	-	16 x 6mm relays. 20-pole connector	TIAL F20 16X1CO	-	1463550000		
	-		-	-	-	8 x 12mm relays. 10-pole connector	TIAL F10 8X2CO	-	1463540000		
	-		-	-	-	Partition Plate	TXL PP	-	2774090000		
	-		-	-	-	Feedthrough module	TXPL FT	-	2774080000		
	-		-	-	-	Supply module	TXPL S	-	2774100000		

Series / family		Colour	2-pole	10-pole	51-pole	Series / family	26-pole
1CO (6mm wide relay)		Orange	2556350000	2556360000	2556370000	2CO (12mm wide relay)	2556380000
		Red	2556390000	2556400000	2556410000		2556420000
		Blue	2556430000	2556440000	2556450000		2556460000
		Black	2556470000	2556480000	2556490000		2556500000

*Resistive load rating only. For inductive loads please see relay selection guide

General Relays

General purpose industrial relays. Compact relays for use in general purpose switching applications with a wide selection of stocked models suited to your load.

Series / family		Coil Voltage	Load Max	Contacts	Contact material	Application	Description	Part Number
DRI Industrial relay - 1 C/O with Test button, LED, diode* (DC)		12V DC	10A	1CO	AgSnO	General Purpose Industrial Relay	DRI 12VDC LDT/1CO	7760056314
		24V DC					DRI 24VDC LDT/1CO	7760056315
		48V DC					DRI 48VDC LDT/1CO	7760056316
		110V DC					DRI 110VDC LDT/1CO	7760056317
		24V AC					DRI 24VAC LT/1CO	7760056318
		115V AC					DRI 115VAC LT/1CO	7760056319
		230V AC					DRI 230VAC LT/1CO	7760056320
DRI Industrial relay - 2 C/O with Test button, LED, diode* (DC)		12V DC	5A	2CO			DRI 12VDC LDT/2CO	7760056339
		24V DC					DRI 24VDC LDT/2CO	7760056340
		48V DC					DRI 48VDC LDT/2CO	7760056341
		110V DC					DRI 110VDC LDT/2CO	7760056342
		24V AC					DRI 24VAC LT/2CO	7760056343
		115V AC					DRI 115VAC LT/2CO	7760056344
		230V AC					DRI 230VAC LT/2CO	7760056345

Series / family	Type	Description	Part Number	Description	Cross Connect	Cross connect
Base DRI		PUSH-IN	SDI 1CO P	SCM/SDI P CC	2 way	7760056366
		Screw	SDI 1CO	SRC-I QV S	8 way	1132070000
		PUSH-IN	SDI 2CO P	SCM/SDI P CC	2 way	7760056366
		Screw	SDI 2CO	SRC-I QV S	8 way	1132070000

Series / family		Coil Voltage	Load Max	Con- tacts	Contact material	Application	Description	Part Number
DRM Industrial relay - 2 C/O with Test button, LED, diode* (DC)		12V DC	10A	2CO	AgNi	General Purpose Industrial Relay	DRM 12VDC 2CO LT	7760056068
		24V DC					DRM 24VDC 2CO LT	7760056069
		48V DC					DRM 48VDC 2CO LT	7760056070
		110V DC					DRM 110VDC 2CO LT	7760056071
		24V AC					DRM 24VAC 2CO LT	7760056073
		115V AC					DRM 115VAC 2CO LT	7760056075
		230V AC					DRM 230VAC 2CO LT	7760056076
DRM Industrial relay - 4 C/O with Test button, LED, diode* (DC)		12V DC	5A	4CO			DRM 12VDC 4CO LT	7760056096
		24V DC					DRM 24VDC 4CO LT	7760056097
		48V DC					DRM 48VDC 4CO LT	7760056098
		110V DC					DRM 110VDC 4CO LT	7760056099
		24V AC					DRM 24VAC 4CO LT	7760056101
		115V AC					DRM 115VAC 4CO LT	7760056103
		230V AC					DRM 230VAC 4CO LT	7760056104

Series / family	Type	Description	Part Number	Description	Cross Connect	Cross connect
Base DRM		PUSH-IN	SCM 2CO P	SCM/SDI P CC	2 way	7760056366
		Screw	SCM 2CO ECO	SCM-I QV S	8 way	1132080000
		PUSH-IN	SCM 4CO P	SCM/SDI P CC	2 way	7760056366
		Screw	SCM 4CO ECO	SCM-I QV S	8 way	1132080000

Series / family		Coil Voltage	Load Max	Contacts	Contact material	Application	Description	Part Number
Safeseries Forcibly Guided Relays		24V DC	6A	3NO1NC	AgSnO + Au	Forcibly Guided Safety relay	FSKIT 24VDC 3NO1NC FG LD	2759070000
				2NO2NC			FSKIT 24VDC 2NO2NC FG LD	2759080000
				4NO2NC			FSKIT 24VDC 4NO2NC FG LD	2759090000
				3NO3NC			FSKIT 24VDC 3NO3NC FG LD	2759100000
				5NO1NC			FSKIT 24VDC 5NO1NC FG LD	2860020000
MICROOPTO Special Loads		24V DC	10A	1NO	Power MOSFET	10A Solenoid driver	MOS 24VDC/5-33VDC 10A	8937940000
			2A			2A Solenoid driver	MOS 24VDC/8-30VDC 2A	8937970000
			50mA		Transistor	High switching frequency	MOS 12-24VDC 100KHZ	8937990000
Timer Relays		24-230V AC/DC	5A	1CO	AgNi	Timer: on-delay, off-delay, single shot, clock generator, flip-flop. 0-10 h	ITS 24-240VUC 1CO M7C	2496190000
		12-230V AC/DC	8A			Timer: on-delay, off-delay, single shot, clock generator, flip-flop. 0-100 h	TFIS 12-240VUC 1CO M7C	2697250000

Signal Conditioning

Interface between analogue signals and control. The ACT20 series of analogue signal converters provide a wide range of conversion and isolation solutions for typical industry instrumentation or process requirements.



Series / family	Input Type	Output Type	Channels (in/out)	Size	Application	Power	Description	Part Number			
ACT20 Series	 ACT20M	4-20mA	4-20mA	1/1	6mm	General isolation	24VDC	ACT20M-CI-CO-S	1175980000		
				1/2				ACT20M-CI-2CO-S	1175990000		
				1/1	12mm	HART transparent		ACT20P-CI-CO-S	7760054114		
				1/2		HART splitter		ACT20P-CI-2CO-S	7760054115		
				2/2		HART transparent		ACT20P-2CI-2CO-12-S	7760054117		
				1/1	6mm	Active input		Output loop	ACT20M-CI-CO-OLP-S	1176040000	
				2/2			ACT20M-2CI-2CO-OLP-S		1176050000		
				1/1	12mm	General isolation	ACT20P-CI2-CO-OLP-S		7760054119		
				1/2			Loop splitter		ACT20P-CI-2CO-OLP-S	7760054122	
				1/1	6mm	General isolation	Input loop	ACT20M-CI-CO-ILP-S	1176070000		
				2/2				ACT20M-2CI-2CO-ILP-S	1176080000		
				1/1				12mm	ACT20P-CI-CO-ILP-S	7760054123	
		2/2	ACT20P-2CI-2CO-ILP-S	7760054124							
		0-10V 4-20mA	0-10V 4-20mA	1/1	6mm	Active input	24VDC	ACT20M-AI-AO-S	1176000000		
				1/2				Passive input	ACT20M-AI-AO-E-S	1176010000	
				1/1	12mm	Active input splitter		ACT20M-AI-2AO-S	1176020000		
								6mm	Active Input	ACT20P-AI-AO-DC-S	1477420000
					Universal Input	4-20mA		Universal programmable isolator	Output Loop	ACT20M-UI-AO-S	1176030000
	2 x 1CO Relay									1/2	22mm
	0-300VDC 0-100mA			0...±20mA 0...±10V		12mm	Universal V/I converter push-button configurable	24-230V AC/ DC	ACT20P-PRO DCDC II-S	1481970000	
	RTD			0-10V 4-20mA	1/1	6mm	Temperature Transducer	24VDC	ACT20M-RTI-AO-S	1375510000	
									Thermocouple	ACT20M-TCI-AO-S	1375480000
		RTD Thermocouple	4-20mA						Output loop	ACT20M-RTCI-CO-OLP-S	1435590000
	RTD Thermocouple Resistance Potentiometer	0...±20mA 0...±10V	12mm	Universal temperature converter push-button configurable		24-230V AC/ DC	ACT20P-PRO RTCI-AO-DO-S	2448100000			
	0-10A AC/DC 0-30A AC/DC 0-60A AC/DC	0-10V 4-20mA 1CO Relay					17mm	Direct Connect	24VDC	ACT20P-CML-10-AO-RC-S	2044850000
								Hall Effect Current Transducer		ACT20P-CMT-10-AO-RC-S	1510470000
				ACT20P-CMT-30-AO-RC-S		1510540000					
	0-660VDC 0-440VAC	0-10V 4-20mA	22mm			Voltage measurement	24-230V AC/ DC	ACT20P-VM-AO-S	7760054306		
								1phase Phase Monitoring Relay	ACT20P-VMR-1PH-H-S	7760054164	
						0-400VAC 200-480VAC	2 x 1CO Relay	1/2	3phase Phase Monitoring Relay	Line powered	ACT20P-VMR-3PH-ILP-H-S
	ACT20X Hazardous Area	 ACT20X	Digital in	Digital out	1/1	22mm	Limit switches, NAMUR from hazardous to safe area	24VDC	ACT20X-HDI-SDO-S	8965360000	
2/2					ACT20X-HDI-SDO-RNO-S				8965340000		
Safe Digital in			Hazardous Digital out	1/1	Drive solenoids, valves, Alarms in the hazardous area		ACT20X-2HDI-2SDO-S		8965390000		
				2/2			ACT20X-2HDI-2SDO-RNO-S		8965370000		
Hazardous Analogue in			Safe Analogue Out	1/1	Analogue sensor from hazardous to safe area		ACT20X-SDI-HDO-L-S		8965400000		
				2/2			ACT20X-SDI-HDO-H-S		8965410000		
Safe Analogue in			Hazardous Analogue Out	1/1	Driving analogue valve in hazardous area		ACT20X-2SDI-2HDO-S		8965420000		
				2/2			ACT20X-HAI-2SAO-S		8965430000		
Hazardous Temperature in			Safe Analogue Out	1/1	RTD, Thermocouple from hazardous to safe analogue		ACT20X-2HAI-2SAO-S		8965440000		
				2/2			ACT20X-SAI-HAO-S		8965450000		
Universal in			Safe Analogue Out	1/1	Universal hazardous input to safe analogue output		ACT20X-2SAI-2HAO-S		8965460000		
									ACT20X-HTI-2SAO-S	8965470000	
									ACT20X-2HTI-2SAO-S	8965480000	
									ACT20X-HUI-2SAO-S	8965490000	
TTA		Universal Input	0-10V 4-20mA 2 x 1CO Relay	1/1	45 mm	Universal frequency/process transducer with relay outputs	18-264 V AC/ DC	WAS 6 TTA	8939670000		
CBX200								CBX200 USB	8978580000		

● Requires CBX200 PC programming cable



Process Displays

Simple monitoring of analogue instruments with ACT20D. The universal range of indicators in the ACT20D series allows for measurement, display and alarming of typical process signals from analogue instruments.



Series / family	Input Type	Output	Power	Display	Application	Configuration	Mounting	Description	Part Number	
Process Displays		4-20mA	-	Loop Powered	LCD ±9999, with backlight	Analogue process loop indicator, easy viewing in bright or dark installations	Push button programming	Panel mount 1/8 DIN, IP65 front	ACT20D-LCD-CHLP	2920000000
		4-20mA, 0-10V, 0-10kΩ Potentiometer, RTD, Thermocouple	-	21-253 VAC, 19.2-300 VDC	Red LED, 4 digit (-1999 to 9999)	Universal process indicator			ACT20D-LED-UI-AC-DC	2920050000
						Universal process indicator with programmable relay alarms and analogue output			ACT20D-LED-UI-AO-4RC-AC-DC	2920060000
						Frequency indicator, for measuring motor rotation, relay alarm for under/over speed, frequency to analogue conversion			ACT20D-LED-FI-AO-2RC-AC-DC	2920070000
		Frequency: NPN/PNP, TTL, Namur, Contact, Tacho, 0-50kHz	4-20mA, 2xCO relay							

Series / family	Output	Description	Part Number
Accessories		Extra protection for extreme environments. Flexible PVC	2964330000



Surge Protection

Full protection for power, instrumentation and data. Choose from a large number range of surge protection devices to suit your protection requirements.


Series / family		Network	Voltage	N-E Combined (MEN)	I _{max} (8/20us)	Application	Fault Contact	Description	Part Number		
Power Protection - VPU AC		3-phase	240 / 415VAC	●	100kA	Main Switchboard (High Exposure) Category C	Yes	VPU AC I 3 R 275/25 MB	2774960000		
			-	-				VPU AC I 3+1 R 275/25 MB	2638070000		
		1-phase	240 VAC	-				VPU AC I 1+1 R 275/100kA MB	2775000000		
			3-phase	240 / 415VAC	●	50kA		Sub distribution board (Medium Exposure) Category B	VPU AC I 1 R 275/100kA MB	2774940000	
		1-phase		240 VAC	●				VPU AC II 3 R 300V/50	2591170000	
			-	-	VPU AC II 3+1 R 300V/50				2591090000		
		120 VAC	-	3kA	Final circuit or machine (Low Exposure) Category A	Yes		VPU AC II 1+1 R 300V/50	2591070000		
			DC					240 VAC	●	VPU AC II 1 R 300V/50	2591030000
								48 VDC	-	VPU AC II 1 300V/50	2591020000
		24 VDC	-	2kA	Final circuit or machine (Low Exposure) Category A		VPU AC II 1 300V/50	2591020000			
			12 VDC			-	VPU III R 120V/6KV AC/DC	1351630000			
						-	VPU III R 48V/4KV AC/DC	1351600000			
-	-					VPU III R 24V/4KV AC/DC	1351580000				
Power Protection - VPU AC with built-in fuse		1-phase	240 VAC	●	65kA	Main Switchboard (built-in fuse) Category B	Yes	VPU AC I F 1 R 275/25	2859340000		
			3-phase	240 / 415VAC				-	40kA	Sub distribution board (built-in fuse) Category B	VPU AC II F 3 R 300/40
		-		-	VPU AC II F 3+1 R 300/40	2807440000					
		1-phase	240 VAC	-	VPU AC II F 1+1 R 300/40	2807430000					
			●	-	VPU AC II F 1 R 300/40	2807390000					
Compact Power Supply Surge Protection		1-phase	240 VAC	-	20kA	Power supply surge protection Category B	Yes	VPU AC II+III 1+1 R 275/20 S	2907940000		
		3-phase						VPU AC II+III 3 R 275/20 S	2907880000		

Series / family		Network	Voltage	Class	I _{max} (8/20us)	Application	Fault Contact	Description	Part Number
Photovoltaic - VPU PV		Photovoltaic	1000 VDC	I / II	40kA	Photovoltaic Systems (Separation distance not met)	Yes	VPU PV I+II 3 R 1000	2530620000
			1500 VDC		30kA			VPU PV I+II 3 R 1500V	2530590000
			1000 VDC	II	40kA	Photovoltaic Systems (Separation distance met)		VPU PV II 3 R 1000V	2530180000
			1500 VDC		30kA			VPU PV II 3 R 1500V	2530650000
Signal and Instrumentation - VSSC6		Analogue & Digital	30 VAC/DC	-	5kA	For current and voltage loops	No	VSSC6 CL 24VUC 0.5A	1064170000
			-	-	10kA	For digital signals		VSSC6 SL LD 24VUC 0.5A	1064350000
			15 VDC	-		RS485 2-wire		VSSC6 RS485	1064980000
			12 VDC	-		RS232 2-wire		VSSC6 RS232	1064990000
			24 VAC/DC	-	1kA	MOV protection for 24V devices		VSSC6 MOV 24VUC	1064540000
RJ45 Protection - VDATA		Data	48 VDC	-	10kA	Cat6A cabling, suitable for PoE devices to 802.3at/af/bt	No	VDATA CAT6	1348590000

Heavy Duty Connectors

Safe and reliable transmission of power, signals and data in industrial environments.

Weidmüller's RockStar heavy duty connectors offer a robust pluggable connection from cabinet to field.



Series / family		Poles	Insert Socket Female		Insert Plug Male		Bulkhead Base	Surface Base	Hood Side Entry	Hood Top Entry	Cable Gland	
			Screw	PUSH-IN	Screw	PUSH-IN						
Rockstar HDC			4	1498400000	-	1498300000	-	1497600000	-	-	1788820000	1772220000
				HDC HA 4 F		HDC HA 4 M		HDC 04A ALU	-	-	HDC 04A TOLU 1M20G	VG M20 - MS 68
			6	1200200000	1873520000	1200000000	1873530000	1202500000	1900360000	1788100000	1788120000	1772220000
				HDC HE 6 F		HDC HE 6 M		HDC 06B ADLU	HDC 06B SDLU 1M20G	HDC 06B TSLU 1M20G	HDC 06B TOLU 1M20G	VG M20 - MS 68
			10	1204100000	1873540000	1203900000	1873550000	1206500000	1903410000	1787580000	1787620000	1772230000
				HDC HE 10 F		HDC HE 10 M		HDC 10B ADLU	HDC 24D SDLU 1M25G	HDC 10B TSLU 1M25G	HDC 10B TOLU 1M25G	VG M25 - MS 68
			16	1207700000	1873560000	1207500000	1873570000	1210100000	1415810000	1788200000	1788230000	1772230000
				HDC HE 16 F		HDC HE 16 M		HDC 16B ADLU	HDC 16B SDLU 1M25G	HDC 16B TSLU 1M25G	HDC 16B TOLU 1M25G	VG M25 - MS 68
			24	1211300000	1873580000	1211100000	1873590000	1214300000	1904440000	1787790000	1787850000	1772240000
				HDC HE 24 F		HDC HE 24 M		HDC 24B ADLU	HDC 64D SDLU 1M32G	HDC 24B TSLU 1M32G	HDC 24B TOLU 1M32G	VG M32 - MS 68

*Other models available in full catalogue

1. Set on the number of poles required.
2. Pick your male and female insert as required in screw or PUSH-IN wiring connection.
3. Finish the kit with the recommended base and cable gland.

ModuPlug modular heavy duty connection system. More power, signal and data connections in less space and exactly what you need.

1. Pick your ModuPlug frame depending on how many insert slots you need. You will need an A-B and B-A frame set.
2. Pick your required inserts, both male and female for either end of the plug.
3. Finish the kit with the recommended base and hood.

Series / family		Slots Max	ModuPlug Frame		Bulkhead Base	Surface Base	Hood Side Entry	Hood Top Entry	Cable Gland
			A-B	B-A					
ModuPlug Housing		2	1428920000	1428940000	1202500000	1900360000	1788100000	1788120000	1772220000
		3	1428960000	1428980000	1206500000	1903410000	1787580000	1787620000	1772230000
		4	1429010000	1429030000	1210100000	1415810000	1788200000	1788230000	1772230000
		6	1429050000	1429070000	1214300000	1904440000	1787790000	1787850000	1772240000

Series / family		Slots Used	Insert		Poles	Current Rated	Connection Type	Wiring Diameter	Rated Voltage
			Male	Female					
ModuPlug Inserts		1	2772820000	2772830000	2	40A	PUSH-IN	10mm²	690V
			2772780000	2772790000	3				
			2772800000	2772810000	4				
			2748320000	2748330000	2	40A	Screw	1000V	
	2748300000	2748310000	2	70A					
	2748280000	2748290000	2	100A					
	2748240000	2748250000	1	200A	70mm²				
	2748400000	2748410000	5	16A		1.5mm²			
	2748460000	2748470000	12	10A	PUSH-IN		230V		
	1	2636180000	2636190000	5		16A		2.5mm²	400V
		2748420000	2748430000	6					500V
		2748440000	2748450000	8			400V		
	1	2592030000	RJ45-RJ45 Coupler Female			-	RJ45 Cat6A	-	-
		2592210000	RJ45 Plug Male			-		-	-
	0.5	1429040000	Dummy Module						

*Other models available in full catalogue

Circular Cordsets

Secure connection of sensors and devices with Weidmüller's SAI range. Explore our wide range of circular connectors suitable for signal, power and data.



Series / family				Size	Poles	Head Gender	Tail Gender	Length	Description	Straight	Angled
Cordsets	           	M8 A-Coded	3	Male	Free	3m	SAIL-M8G-3-3.0U	1824590300	1857550300		
				Female		5m	SAIL-M8G-3-5.0U	1824590500	1857550500		
						10m	SAIL-M8G-3-10U	1824591000	1857551000		
						3m	SAIL-M8BG-3-3.0U	9457450300	9457380300		
						5m	SAIL-M8BG-3-5.0U	9457450500	9457380500		
						10m	SAIL-M8BG-3-10U	9457451000	9457381000		
			4	Male		3m	SAIL-M8G-4-3.0U	1906270300	1857560300		
				5m		SAIL-M8G-4-5.0U	1906270500	1857560500			
				10m		SAIL-M8G-4-10U	1906271000	1857561000			
				3m		SAIL-M8BG-4-3.0U	9457850300	9456150300			
				5m		SAIL-M8BG-4-5.0U	9457850500	9456150500			
				10m		SAIL-M8BG-4-10U	9457851000	9456151000			
		M12 A-Coded	3	Male		3m	SAIL-M12G-3-3.0U	9457810300	9456690300		
				Female		5m	SAIL-M12G-3-5.0U	9457810500	9456690500		
						10m	SAIL-M12G-3-10U	9457811000	9456691000		
						3m	SAIL-M12BG-3-3.0U	9457820300	1061890300		
						5m	SAIL-M12BG-3-5.0U	9457820500	1061890500		
						10m	SAIL-M12BG-3-10U	9457821000	1061891000		
			4	Male		3m	SAIL-M12G-4-3.0U	9456100300	1906260300		
				Female		5m	SAIL-M12G-4-5.0U	9456100500	1906260500		
						10m	SAIL-M12G-4-10U	9456101000	1906261000		
						3m	SAIL-M12BG-4-3.0U	9457730300	9457740300		
						5m	SAIL-M12BG-4-5.0U	9457730500	9457740500		
						10m	SAIL-M12BG-4-10U	9457731000	9457741000		
			5	Male		3m	SAIL-M12G-5-3.0U	9457610300	9457670300		
				Female		5m	SAIL-M12G-5-5.0U	9457610500	9457670500		
						10m	SAIL-M12G-5-10U	9457611000	9457671000		
						3m	SAIL-M12BG-5-3.0U	9457910300	9457690300		
						5m	SAIL-M12BG-5-5.0U	9457910500	9457690500		
						10m	SAIL-M12BG-5-10U	9457911000	9457691000		
		5	Male	10m		SAIL-M12GM12G-5-10U	9457341000	-			
			15m	SAIL-M12GM12G-5-15U		9457341500	-				

Series / family		Size	Connection Type	Poles	Outlet Type	Description	Male	Female
Field Wireable Connectors		M8	Screw	3	Straight	SAIB-M8-3P	1803860000	1803870000
				4		SAIB-M8-4P	1803850000	1803880000
		M12 A-Coded	Screw	5	Straight	SAIS-5/9	1807350000	1807250000
					Angled	SAIBW-5/9	1807370000	1807330000

Tools

With Weidmüller's professional tools, you can work faster, better, and more precisely than ever before.

For over 50 years, we have been developing and manufacturing our comprehensive range of durable, high quality tools to meet the highest demands of cabinet assembly.



Series / family		KT 8	KT 12	KT 22	KT 45 R	KT 55
Cutting Tools						
	Part Number	9002650000	9002660000	1157830000	9202040000	9202060000
	Application	Cable cutter, for copper or aluminium				
	Diameter	8mm	12mm	22mm	45mm	55mm

Series / family		STRIPAX	STRIPAX 16	STRIPAX ULTIMATE
Stripping Tools				
	Part Number	9005000000	9005610000	1468880000
	Application	Flexible and solid conductors with PVC insulation		Flexible and solid conductors with halogen-free or tough insulation
	Cross Section	0.08-10mm ²	6-16mm ²	0.25-6mm ²

Series / family		PZ 6 ROTO	PZ 6 ROTO L	PZ 16	PZ 10 HEX	PZ 50	CTI 6
Crimping Tools							
	Part Number	9014350000	1444050000	9012600000	1445070000	9006450000	9006120000
	Application	Trapezoidal crimp		Indent crimp	Hexagonal crimp	Indent crimp	Insulated Spade and ring lugs
	Diameter	0.14-6mm ²		6-16mm ²	0.25-10mm ²	25-50mm ²	0.5-6mm ²

• With locking button

Series / family		STRIPAX PLUS 2.5	
Stripping and Crimping Tools			
	Part Number	9020000000	
	Application	Cutter, stripper and crimper, uses strips of linked ferrules	
	Cross Section	0.5-2.5mm ²	

Series / family		CUT/STRIP/CRIMP SET	CRIMPSET PZ 10 HEX T	CRIMP-SET PZ 6 ROTO L T	CRIMP-SET STRIPAX PLUS T
Sets					
	Part Number	8000120354	1542270000	9028700000	9028790000
	Contents	Stripax + PZ6 Roto + KT 8 + Screwdriver	PZ 10 HEX + Stripax + Ferrules (0.5 WT, 0.75 LTBL, 1.0 RD, 1.5 BK, 2.5 GY, 4.0 OR, 6.0 GN, 10.0 BRN)	Stripax + PZ6 Roto L + Ferrules (0.5 WT, 0.75 LTBL, 1.0 RD, 1.5 BK, 2.5 GY, 4.00 R, 6.0 GN)	Stripax Plus + Ferrules (0.5 WT, 0.75 LTBL, 1.0 RD, 1.5 BK, 2.5 GY)

*Ferrules Page 28



Tools

With Weidmüller's professional tools, you can work faster, better, and more precisely than ever before. For over 50 years, we have been developing and manufacturing our comprehensive range of durable, high quality tools to meet the highest demands of cabinet assembly.



Series / family		VKSW	TSD 35	TSLD 5
Workplace Tools				
	Part Number	1137530000	1318510000	9918700000
	Application	Duct Cutter	DIN rail cutter	DIN rail cutter and perforator
	Suitable Material	125mm wide duct	TS 35/7.5, TS 35/15	TS 35/7.5, TS 35/15, TS32, TS 15/5.5

Series / family		AM 16	AM 25	AM 35	AM-X
Insulation Stripper					
	Part Number	9204190000	9001540000	9001080000	2625720000
	Application	PVC cable insulation stripper			PVC round cable, unlimited size
	Cable Diameter	5-17mm	6-25mm	25-35mm	25mm-endless

Series / family		SDI SET S2.5-5.5/PH1/2	SDI SET SLIM S3.5-6.5/PH1/2	SD SET S2.5-5.5/PH1/2	SD EL SET 1.5-4.0/PH0/1
Screwdrivers					
	Part Number	2749750000	2749580000	2749200000	2750160000
	Type	Insulated	Slim insulated	Non-insulated	Pico swivelhead
	Contains	PH1 x 80, PX2 x 100, Slotted (2.5 x 75, 3.0 x 100, 4.0 x 100, 5.5 x 125)			PH0 x 60, PH1 x 80, Slotted (1.5 x 40, 2.0 x 60, 2.5 x 75, 3.0 x 75, 4.0 x 100)


Series / family		CROSS-KEY UNIVERSAL	CROSS-KEY-DUO	CROSS-KEY-QUADRO
Cabinet Keys				
	Part Number	9918130000	1480190000	1480180000





Ferrules

Outstanding quality: we ensure long-term connections. Using wire-end ferrules ensures the long-term, consistent quality of your electrical connections. Our wide range of products comprise of single and twin boot wire end ferrules in a variety of sizes and conforming to industry standard colours.



Series / family		Cross Section (mm²)	L1	L2	D2	Stripping Length	Colour	Pack Size	Description	Part Number
Ferrules with Plastic Collars - Packed loose		0.5	14	8	2.6	10	○ White	500 (loose pack)	H0,5/14D W	9019010000
			16	10		12			H0,5/16D W	9019020000
		0.75	14	8	2.8	10	● Grey		H0,75/14D GR	9019040000
			18	12		14			H0,75/18D GR	9019060000
		1.0	14	8	3	10	● Red		H1,0/14D R	9019080000
			18	12		15			H1,0/18D R	9019110000
		1.5	14	8	3.5	10	● Black		H1,5/14D SW	9019120000
			16	10		12			H1,5/16D SW	9019130000
			18	12		15			H1,5/18D SW	9019140000
		2.5	15	8	4.2	10	● Blue		H2,5/15D BL	9019160000
			19	12		14			H2,5/19D BL	9019170000
			25	18		20			H2,5/25D BL	9019180000
		4.0	18	10	4.8	12	● Grey		H4,0/18D GR	9019190000
			20	12		14			H4,0/20D GR	9019200000
			26	18		20			H4,0/26D GR	9019210000
		6.0	20	12	6.3	14	● Yellow		H6,0/20D GE	9019220000
			26	18		20			H6,0/26D GE	9019230000
		10.0	22	12	7.6	15	● Red		H10,0/22D R	9019240000
			28	18		21			H10,0/28D R	9019250000
Ferrules with Wide Collar - Suitable for thicker insulation cable		0.5	14	8	2.9	10	○ White	500 (loose pack)	H0,5/14S W	9004590000
		0.75	14		3.4		● Grey		H0,75/14DS GR	9028580000
		1.0	14		3.5		● Red		H1,0/14S R	9018560000
		1.5	14		4		● Black		H1,5/14DS SW	9025240000

Series / family		Cross Section (mm²)	L1	L2	A	Stripping Length	Colour	Pack Size	Description	Part Number
Twin Boot Ferrules with Plastic Collars - Packed loose		0.5	14	8	5	11	○ White	500	H0,5/14D ZH W	9037380000
			18	12		15			H0,5/18D ZH W	9037400000
		0.75	14	8	5.5	11	● Grey		H0,75/14D ZH GR	9037410000
			16	10		13			H0,75/16D ZH GR	9037420000
		1.0	15	8	5.8	11	● Red		H1,0/15D ZH R	9037440000
			19	12		16			H1,0/19D ZH R	9037450000
			25	18		22			H1,0/25D ZH R	9037460000
		1.5	16	8	6.5	11	● Black		H1,5/16D ZH SW	9037470000
			20	12		15			H1,5/20D ZH SW	9037480000
			26	18		21			H1,5/26D ZH SW	9037490000
		2.5	19	10	8	13	● Blue	500	H2,5/19D ZH BL	9037500000
			21	12		15		H2,5/21D ZH BL	9037510000	
			27	18		21		H2,5/27D ZH BL	9037520000	
		4.0	22	12	9	15	● Grey	100	H4,0/22D ZH GR	9037530000
			28	18		21			H4,0/28D ZH GR	9037540000

Series / family		Cross Section (mm ²)	L1	L2	D2	Stripping Length	Colour	Pack Size	Description	Part Number
Ferrules for Stripax Plus 2.5 - Strip of ferrules 		0.5	14	8	2.6		○ White	500 (strip of ferrules)	H0,5/14D W BD	9004280000
		0.75			2.8		● Grey		H0,75/14D GR BD	9004300000
		1.0			3		● Red		H1,0/14D R BD	9004330000
		1.5			3.5		● Black		H1,5/14D SW BD	9004350000
		2.5			4.2		● Blue		H2,5/14D BL BD	9004360000

Markers and Printers

Convenient, simple, multi-purpose. The Multimark printing system provides a marking solution for the whole cabinet all from the same machine. From terminal marking, wire and cable marking or device label marking, a wide range of options exist for any application.




Series / family		Print Volume	Marking type	Big Pack (BP) support?	Description	Part Number
THM MultiMark Thermal Printer		Small and medium print volumes	Terminal markers, wire markers, adhesive label markers, heatshrink markers	No, external roll holder required*	THM MULTIMARK	2599430000
		Medium to large print volumes		Yes	THM MULTIMARK PLUS	2599440000

Series / family		Width	Application	Length	Description	Part Number
MultiMark Accessories		25mm	Terminal markers (DEK/WS)	360m	RIBBON MM-TB 25/360 BLACK	2005090000
		110mm	Wire markers (TM-H), Label markers		RIBBON MM 110/360 BLACK	2005070000
		60mm	Heatshrink markers	300m	RIBBON MM-HS 60/300 BLACK	2448880000
			External holder for big pack markers		THM MMP EXTENSION*	1302920000

Series / family			Height	Width	Marker Qty	Description	Supported Terminal Size*	A-series support	W-series support	Part Number
Dekafix Multimark			5mm	3.5mm	1000	DEK 5/3.5 MM WS	1.5mm²	●	●	2007100000
					15000	DEK 5/3.5 MM BP WS				2619760000
				5mm	800	DEK 5/5 MM WS	2.5mm²	●	●	2007110000
					10000	DEK 5/5 MM BP WS				2619770000
				6mm	600	DEK 5/6 MM WS	4mm²	●	●	2007120000
					9000	DEK 5/6 MM BP WS				2619780000
				8mm	500	DEK 5/8 MM WS	6mm²	●	●	2007130000
					6000	DEK 5/8 MM BP WS				2619790000

Series / family			Height	Width	Marker Qty	Description	Supported Terminal Size*	A-series support	W-series support	Part Number		
WS Multimark			8mm	3.5mm	1000	WS 8/3.5 MM WS	1.5mm ²	●	●	2007140000		
					11000	WS 8/3.5 MM BP WS				2619800000		
				5mm	800	WS 8/5 MM WS	2.5mm ²	●	●	2007150000		
					8000	WS 8/5 MM BP WS				2619810000		
				6mm	600	WS 8/6 MM WS	4mm ²	●	●	2007160000		
					6000	WS 8/6 MM BP WS				2619820000		
				8mm	500	WS 8/8 MM WS	6mm ²	●	●	2007170000		
					5000	WS 8/8 MM BP WS				2619830000		
					10mm	5mm	800	WS 10/5 MM WS	2.5mm ²	●	●	2712130000
						6mm	600	WS 10/6 MM WS	4mm ²	●	●	2712140000
			12mm	5mm	800	WS 12/5 MM WS	2.5mm ²	-	●	2007190000		
					5500	WS 12/5 MM BP WS				2619850000		
				6mm	600	WS 12/6 MM WS	4mm ²	-	●	2007200000		
					4500	WS 12/6 MM BP WS				2619860000		
				8mm	500	WS 12/8 MM WS	6mm ²	-	●	2007210000		
					3500	WS 12/8 MM BP WS				2619870000		

Series / family		Numbering	Pack Size	Description	Horizontal	Vertical
Preprinted Dekafix 5/5		1-10	5 lines per card, 10 cards per box	DEK 5 FX 1-10	0523060001	0460660001
		11-20		DEK 5 FX 11-20	0523060011	0460660011
		21-30		DEK 5 FX 21-30	0523060021	0460660021
		31-40		DEK 5 FX 31-40	0523060031	0460660031
		41-50		DEK 5 FX 41-50	0523060041	0460660041
		51-60		DEK 5 FX 51-60	0523060051	0460660051
		61-70		DEK 5 FX 61-70	0523060061	0460660061
		71-80		DEK 5 FX 71-80	0523060071	0460660071
		81-90		DEK 5 FX 81-90	0523060081	0460660081
		91-100		DEK 5 FX 91-100	0523060091	0460660091

Markers and Printers

Convenient, simple, multi-purpose. The Multimark printing system provides a marking solution for the whole cabinet all from the same machine. From terminal marking, wire and cable marking or device label marking, a wide range of options exist for any application.



Series / family		Height	Width	Marker Qty	Description	Part Number
TM-I Wire Marker		12mm	4mm	2000	TM-I 12 MM WS	2005440000
		15mm			TM-I 15 MM WS	2005450000
		18mm			TM-I 18 MM WS	2005470000
		20mm			TM-I 20 MM WS	2005490000
		23mm			TM-I 23 MM WS	2005510000
		30mm			TM-I 30 MM WS	2005530000

Series / family		Cable size	Description	Width					
				12mm	15mm	18mm	20mm	23mm	30mm
TM Transparent Sleeve		0.25-1.5mm ²	TM 201	1798640000	1798620000	1798600000	1798580000	1507060000	1874850000
		0.5-2.5mm ²	TM 202	1798560000	1798540000	1798530000	1798520000	1507070000	1874760000
		2.5-10mm ²	TM 203	1798510000	1798490000	1798480000	1798470000	1507080000	1874770000
		6-16mm ²	TM 204	1806180000	1806240000	1806300000	1806360000	1507090000	1874780000
		16-35mm ²	TM 205	1806190000	1806250000	1806310000	1806370000	1507100000	1874790000
		35-120mm ²	TM 206	1806200000	1806260000	1806320000	1806380000	1507110000	1874800000

Series / family		Cable size	Width	Description	Marker Qty	White	Yellow
Heatshrink Cable Marker - Standard		0.5-1.5mm ²	12mm	HS 1.0-3.2/12 MM	4000	2526070000	2526080000
			25mm	HS 1.0-3.2/25 MM	2000	2437510000	2437520000
		1.5-4mm ²		HS 1.6-4.8/25 MM	2000	2437550000	2437560000
		4-16mm ²		HS 3.2-9.5/25 MM	1000	2437670000	2437680000
Heatshrink Cable Marker - Halogen Free		0.5-1.5mm ²	25mm	HSS-HF 1/8 1.8-2.8/25Y	10,000	-	1961970000
		1.5-4mm ²		HSS-HF 3/16 2.8-4.2/25Y	8000	-	1961980000
		4-10mm ²		HSS-HF 1/4 4.2-5.8/25Y	5000	-	1961990000
		10-16mm ²		HSS-HF 3/8 5.8-8.0/25Y	4000	-	1962000000

Series / family		Height	Width	Description	Marker Qty	White	Yellow	Silver
MT30X Adhesive Device Marker		6	15	THM MT30X 15/6	10,000	1753231044	1753231687	1753230001
		9	15	THM MT30X 15/9		1058750000	1058740000	-
		9	17	THM MT30X 17/9		1968130000	1856650000	1356500000
		8	20	THM MT30X 20/8		1753241044	1753241687	-
		10	20	THM MT30X 20/10		2556240000	-	-
		12	25	THM MT30X 25/12		1751751044	1751751687	-
		20	30	THM MT30X 30/20	6000	1753261044	1753261687	1753260001
		19	38	THM MT30X 38/19	2000	1751801044	1751801687	-
		35	65	THM MT30X 65/35	1000	1751831044	1751831687	1751830001
		48	101	THM MT30X 101/48	500	1751821044	1751821687	1751820001

Series / family		Height	Width	Description	Marker Qty	White	Yellow
SFX Cable Marker		9	24	SFX 9/24 MM	1000	2005320000	2005380000
		11	60	SFX 11/60 MM		2005340000	2005400000

Cable Entry Systems

Cabtite - the modular cable entry system. With the Cabtite cable entry system, assembled cables can be quickly and easily installed into an enclosure through the use of split sealing glands and frames which provide protection up to IP66.



Series / family		Installation	Protection Class	Frame Size	Description	Part Number
Cabtite Frame		Cabtite Standard Frame - Installation from inside enclosure	IP66	4 x small or 1 x large	CABTITE FR 4-1 BK SET	2583780000
				6 x small or 1 x large + 2 small	CABTITE FR 10/6 BK SET	2583760000
				8 x small or 2 x large or 1 x large + 4 x small	CABTITE FR 16/8 BK SET	2583740000
				10 x small or 1 x large + 6 small or 2 x large + 2 small	CABTITE FR 24/10 BK SET	2583720000
		Cabtite FrontTight - Installation from outside enclosure	IP66	4 x small or 1 x large	CABTITE FRFT 4-1 SET	2891470000
				6 x small or 1 x large + 2 small	CABTITE FRFT 10/6 SET	2891500000
				8 x small or 2 x large or 1 x large + 4 x small	CABTITE FRFT 16/8 SET	2891530000
				10 x small or 1 x large + 6 small or 2 x large + 2 small	CABTITE FRFT 24/10 SET	2891560000

Series / family		Colour	Material	Number of Entries	Clamping Range	Description	Part Number
Cabtite Sealing Element - Small		Black	TPE, halogen free, Flammability rating: HB, UV Stabilised	1	1.5...2 mm	CABTITE SE 1.5-2 SML	2584780000
					2...3 mm	CABTITE SE 2-3 SML	2584760000
					3...4 mm	CABTITE SE 3-4 SML	2584730000
					4...5 mm	CABTITE SE 4-5 SML	2584680000
					5...6 mm	CABTITE SE 5-6 SML	2584710000
					6...7 mm	CABTITE SE 6-7 SML	2584690000
					7...8 mm	CABTITE SE 7-8 SML	2584670000
					8...9 mm	CABTITE SE 8-9 SML	2584330000
					9...10 mm	CABTITE SE 9-10 SML	2584080000
					10...11 mm	CABTITE SE 10-11 SML	2584060000
					11...12 mm	CABTITE SE 11-12 SML	2584040000
					12...13 mm	CABTITE SE 12-13 SML	2584020000
					13...14 mm	CABTITE SE 13-14 SML	2584000000
					14...15 mm	CABTITE SE 14-15 SML	2583980000
					15...16 mm	CABTITE SE 15-16 SML	2583960000
				2	4...5 mm	CABTITE SE 2/4-5 SML	2583620000
					5...6 mm	CABTITE SE 2/5-6 SML	2583610000
					7...8 mm	CABTITE SE 2/7 SML	2583550000
				3	8...9 mm	CABTITE SE 2/8 SML	2583540000
					5...6 mm	CABTITE SE 3/5-6 SML	2652280000
				4	2...3 mm	CABTITE SE 4/2-3 SML	2583590000
					3...4 mm	CABTITE SE 4/3-4 SML	2583580000
					4...5 mm	CABTITE SE 4/4-5 SML	2583560000
				0	Blanking plug	CABTITE BSE SML	2584790000

Series / family		Colour	Material	Number of Entries	Clamping Range	Description	Part Number
Cabtite Sealing Element - Large		Black	TPE, halogen free, Flammability rating: HB, UV Stabilised	1	14...15 mm	CABTITE SE 14-15 LRG	2583880000
					15...16 mm	CABTITE SE 15-16 LRG	2583860000
					16...17 mm	CABTITE SE 16-17 LRG	2583850000
					17...18 mm	CABTITE SE 17-18 LRG	2583840000
					18...19 mm	CABTITE SE 18-19 LRG	2583830000
					19...20 mm	CABTITE SE 19-20 LRG	2583810000
					20...21 mm	CABTITE SE 20-21 LRG	2583790000
					21...22 mm	CABTITE SE 21-22 LRG	2583770000
					22...23 mm	CABTITE SE 22-23 LRG	2583750000
					23...24 mm	CABTITE SE 23-24 LRG	2583730000
					24...25 mm	CABTITE SE 24-25 LRG	2583710000
					25...26 mm	CABTITE SE 25-26 LRG	2583700000
					26...27 mm	CABTITE SE 26-27 LRG	2583690000
					27...28 mm	CABTITE SE 27-28 LRG	2583680000
					28...29 mm	CABTITE SE 28-29 LRG	2583670000
					29...30 mm	CABTITE SE 29-30 LRG	2583660000

*V0 Sealing elements available on request

Weidmüller – Your partner in Smart Industrial Connectivity

Be it manufacturing, energy production or water management - hardly any of today's industries can do without electronics and electrical connectivity. Our industrial environment is full of devices that need to be connected, controlled, and optimised. We are absolutely committed to always providing the best connection possible. This is demonstrated in our products and the human connections we maintain: We develop solutions in close cooperation with our valued Australian customers which meet the full measure of all requirements of their industrial environment. Industrial Connectivity needs smart connections. And that's precisely what we stand for.

We cannot guarantee that there are no mistakes in the publications or software provided by us to the customer for the purpose of making orders. We try our best to quickly correct errors in our printed media.

All orders are based on our general terms of delivery, which can be reviewed on the websites of our group companies where you place your order. On demand we can also send the general terms of delivery to you.



Weidmüller Pty Ltd (Head Office)

43 Huntingwood Drive,
Huntingwood, NSW, 2148, Australia
T +61 (0) 2 9671 9999
E sales@weidmuller.com.au
www.weidmuller.com.au

Your direct contact

Geoff Thomson

Area Manager, New Zealand
M +64 (0) 21 858196
E geoff.thomson@weidmueller.com



Cuthbert Stewart Limited

22 Fisher Crescent, Mount Wellington
Auckland 1060 New Zealand
T +64 9 928 1000
E support@csl-online.nz
www.csl-online.nz